BRYANT®

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Three Pole, 30A 600V AC, Side Wired Only, Black

By Bryant Catalog # 30003D

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Three Pole, 30A 600V AC, Side Wired Only, Black

General

Environmental Conditions

Item Type Load Capacity Material - Mounting Hardware Number Of Poles OEM Brand Name Operating Cycles Operating Temperature

Series Style Type UPC

Dimensions

Display Size

Indoor Dry Unless Protected By Additional Means Open Switch Inductive Screw Mounting 3 Pole Hubbell Bryant 10,000 Cycles Minimum Minimum Continuous -40 Deg C without Impact Standard Toggle Motor Controller/Disconnect Back & Side Wire 781786631533

Standard Sized Product



Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Phase	Three Phase
Voltage Rating	600V AC kV
Voltage Rating Description	600V AC kV
Wattage	18000
Logistics	
Carton Quantity	10
Product Assets	
Catalog Page - Bryant E-12 Catalog page	
Catalog Page - Bryant G-6 Catalog page	
Catalog Page - Bryant G-2 Catalog page	
Catalogs - Bryant Full Line Catalog	
Literature - General Literature - Motor Controllers and Disconnects	
Literature - General Literature - BRYANT® Wiring Devices	



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. BRY_30003D_SPEC | REV 3/2023