

Straight Blade Devices



TECH-SPEC® Plugs and Connectors

15A and 20A 125V and 250V Plugs and Connectors, 2-Pole 3-Wire Inches (mm)

TECH-SPEC®



Device Type		Plug			Connector	
		Standard	Watertight	Angle 12 Position	Standard	Watertight
	Cord Diameter	.245"-.655" (6.2-16.6)	.300"-.655" (7.6-16.6)	.300"-.655" (7.6-16.6)	.245"-.655" (6.2-16.6)	.300"-.655" (7.6-16.6)
	Rating	Thermoplastic	Elastomeric	Nylon	Thermoplastic	Elastomeric
NEMA 5-15, 15A 125V 	Color					
	Black	5266B	BRY14W47BK	—	5269B	—
	Gray	5266BGRY	—	—	—	—
	Yellow	5266BY	BRY14W47	—	5269BY	BRY15W47
	Black/White	—	—	5295	—	—
	Hi-Viz Green	5156HVG*	—	—	5159HVG*	—
	Hi-Viz Orange	5156HVO*	—	—	5159HVO*	—
NEMA 5-20, 20A 125V 	Black	5364B	—	—	5369B	—
	Gray	—	—	—	—	—
	Yellow	5364BY	BRY14W33	—	5369BY	BRY15W33
	Black/White	—	—	5395	—	—
NEMA 6-15, 15A 250V 	Yellow	—	BRY14W49	—	—	BRY15W49
	Black/White	—	—	5695	—	—
	Black	5666B	—	—	5669B	—
NEMA 6-20, 20A 250V 	Yellow	—	BRY14W48	—	—	BRY15W48
	Black/White	—	—	5475N	—	—
	Black	5464B	—	—	5469B	—

Note: *Hi-Viz green and orange devices are shipped in a display pack.

Weather Protective Accessories



		Weather Protective Boots		Sealing Ring
		For Use with 5266B Series Plug	For Use with 5269B Series Connector	For Use with 5200BC Series Connector Boot
Material	Color			
Thermoplastic	Black	5200BPB**	5200BCB**	5200BSRB**
elastomer	Yellow	5200BP**	5200BC**	5200BSR**

Note: **Not UL Listed or CSA Certified.

Product Dimensions Inches (mm)

		Plug		
		Standard	Watertight	Angled Plug
A	1.53" (38.9)	—	—	1.25" (31.8)
B	2.10" (53.3)	—	3.16" (80.3)	2.07" (52.6)
C	1.38" (35.1)	—	1.85" (47.1)	—
		Connector		
		Standard	Watertight	
A	1.53" (38.9)	—	—	
B	2.68" (68.1)	—	4.42" (112.1)	
C	1.38" (35.1)	—	1.85" (47.1)	

