BRYANT®

Locking Devices, Industrial, Flush Receptacle, 20A 250V, 2-Pole 3-Wire Grounding, L6-20R, Screw **Terminal, Black**

By Bryant Catalog # 70620FR

Locking Devices, Industrial, Nylon Flush Receptacle, 20A 250V, 2-Pole 3-Wire Grounding, L6-20R, Screw Terminal, Black/White

Features

- Combination back and side wiring terminals accept #14 through #8 AWG solid or stranded conductors
- Heavy duty mounting straps are nickel-plated to resist corrosion, wide width design assures secure assembly
- NEMA rating and configuration are molded into face for easy identification
- One-piece, rivetless copper-alloy contact design reduces heat buildup and provides secure blade retention

Application

Extra Heavy Duty Industrial Specification Grade

General

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	20A Single Nylon Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Bryant
Style	Single Receptacle
Туре	Receptacle
UPC	781786689237

Dimensions

Dimensions	3.28 in x 1.70 in x 1.24 in
Display Size	Standard Sized Product
Height	1.24 in
Length	3.28 in
Width	1.70 in



Electrical Ratings

Amperage Rating	20 A	
Connectivity	Terminal Screws	
Current Rating	20 A	
Phase	Single Phase	
Voltage Rating	250 V	
Voltage Rating Description	250V	
Conductor Related		
Number Of Wires	3-Wire	
Wire Size	#14 AWG to #8 AWG	
Certifications and Compliance		
Nema Rating	L6-20R	
Logistics		
Carton Quantity	10	
Product Assets		
Catalog Page - Bryant H-8 Catalog page Catalog Page - Bryant Q-18 Catalog page Catalogs - Bryant Full Line Catalog Literature - General Literature - Healthcare Solutions Literature - General Literature - Power Disruption Solutions Literature - General Literature - BRYANT* Wiring Devices		

HUBBELL

A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. BRY-70620FR-SPEC-EN | REV 5/2023

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com