



## Locking Devices, Industrial, Flush Receptacle, 30A 250V, 2-Pole 3-Wire Grounding, L6-30R, Screw Terminal, Black

By Bryant  
Catalog # [70630FR](#)

Locking Devices, Industrial, Flush Receptacle, 30A 250V, 2-Pole 3-Wire Grounding, L6-30R, Screw Terminal, Black



### Features

- Combination back and side wiring terminals accept #14 through #8 AWG solid or stranded conductors
- Heavy duty mounting straps are nickel-plated to resist corrosion, wide width design assures secure assembly
- NEMA rating and configuration are molded into face for easy identification
- One-piece, rivetless copper-alloy contact design reduces heat buildup and provides secure blade retention

### Application

Extra Heavy Duty Industrial Specification Grade

### General

|                              |   |
|------------------------------|---|
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means |
| Item Type                    | 30A Single Nylon Receptacle                     |
| Material                     | Composite                                       |
| Material - Mounting Hardware | Screw Mounting                                  |
| Number Of Poles              | 2-Pole  |
| OEM Brand Name               | Hubbell Bryant                                  |
| Style                        | Single Receptacle                               |
| Type                         | Receptacle                                      |
| UPC                          | 781786689435                                    |

### Dimensions

|              |                             |
|--------------|-----------------------------|
| Dimensions   | 3.28 in x 1.70 in x 1.24 in |
| Display Size | Standard Sized Product      |
| Height       | 1.24 in                     |
| Length       | 3.28 in                     |
| Width        | 1.70 in                     |

### Electrical Ratings

|                            |                 |
|----------------------------|-----------------|
| Amperage Rating            | 30 A            |
| Connectivity               | Terminal Screws |
| Current Rating             | 30 A            |
| Phase                      | Single Phase    |
| Voltage Rating             | 250 V           |
| Voltage Rating Description | 250V            |

### Conductor Related

|                 |                   |
|-----------------|-------------------|
| Number Of Wires | 3-Wire            |
| Wire Size       | #14 AWG to #8 AWG |

### Certifications and Compliance

|             |        |
|-------------|--------|
| Nema Rating | L6-30R |
|-------------|--------|

### Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

### Product Assets

[Catalog Page - Bryant H-11 Catalog page](#)  
[Catalog Page - Bryant L-10 Catalog page](#)  
[Catalog Page - Bryant Q-18 Catalog page](#)  
[Catalogs - Bryant Full Line Catalog](#)  
[Literature - General Literature - Healthcare Solutions](#)  
[Literature - General Literature - Power Disruption Solutions](#)  
[Literature - General Literature - BRYANT® Wiring Devices](#)

### Related Products

[70630NPB - Locking Devices, Industrial, Male Plug, 30A 250V, 2-Pole 3-Wire Grounding, L6-30P, Screw Terminal, Black](#)  
[70630NP - Locking Devices, Industrial, Male Plug, 30A 250V, 2-Pole 3-Wire Grounding, L6-30P, Screw Terminal, Black and White](#)  
[20405 - Wallplates and Boxes, Weatherproof Covers, 1- Gang, For 30A Power Interrupting, Standard Size, Cast Aluminum, New Style](#)  
[7420B - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1\) 1.62" Opening, Standard Size, Cast Aluminum](#)  
[SB720 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1\) 1.60" Opening, Standard Size, Brass](#)