



**Locking Devices, Industrial, Flush**  
**Receptacle, 30A 3-Phase Delta**  
**250V AC, 3-Pole 4-Wire**  
**Grounding, L15-30R, Screw**  
**Terminal, Black**

By Bryant  
 Catalog # [71530FR](#)

Locking Devices, Industrial, Flush Receptacle, 30A 3-Phase  
 Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30R, Screw  
 Terminal, Black



**Features**

- Combination back and side wiring terminals accept #14 through #8 AWG solid or stranded conductors
- Heavy duty mounting straps are nickel-plated to resist corrosion, wide width design assures secure assembly
- NEMA rating and configuration are molded into face for easy identification
- One-piece, rivetless copper-alloy contact design reduces heat buildup and provides secure blade retention

**Application**

Extra Heavy Duty Industrial Specification Grade

**General**

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	30A Single Nylon Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Bryant
Style	Single Receptacle
Type	Receptacle
UPC	781786696136

**Dimensions**

Dimensions	3.28 in x 1.70 in x 1.24 in
Display Size	Standard Sized Product
Height	1.24 in
Length	3.28 in
Width	1.70 in

**Electrical Ratings**

Amperage Rating	30 A
Connectivity	Terminal Screws
Current Rating	30 A
Phase	Three Phase
Voltage Rating	3 Phase 250 VAC
Voltage Rating Description	3 Phase 250V AC

**Conductor Related**

Number Of Wires	4-Wire
Wire Size	#14 AWG to #8 AWG

**Certifications and Compliance**

Nema Rating	L15-30R
-------------	---------

**Logistics**

Carton Quantity	10
-----------------	----

**Product Assets**

[Catalog Page - Bryant H-12 Catalog page](#)  
[Catalog Page - Bryant Q-18 Catalog page](#)  
[Catalogs - Bryant Full Line Catalog](#)

**Related Products**

[71530NP - Locking Devices, Industrial, Male Plug, 30A 3- Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30P, Screw Terminal, Black and White](#)  
[20405 - Wallplates and Boxes, Weatherproof Covers, 1- Gang, For 30A Power Interrupting, Standard Size, Cast Aluminum, New Style](#)  
[7420B - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1\) 1.62" Opening, Standard Size, Cast Aluminum](#)  
[SS720 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1\) 1.60" Opening, Standard Size, Stainless Steel](#)  
[SB720 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1\) 1.60" Opening, Standard Size, Brass](#)