BRYANT[®]

Locking Devices, Industrial, Flush Receptacle, 20A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, L16-20P, Screw Terminal, Black and White

By Bryant Catalog # 71620NP

Locking Devices, Industrial, Male Nylon Plug,20A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, L16-20P, Screw Terminal, Black and White

Features

- Hand grip features wide-rib, non-slip design
- Configuration-specific plug face surrounds blades to prevent infiltration of contaminants
- Captive, combination Slot/Phillips assembly screws
- Double wall construction for extra durability
- Neutral blade is nickel-plated for easy identification
- Internal "self-centering" Triple Gripper® cord grip with "radius teeth" design provides secure cord retention

Application

Extra Heavy Duty Industrial

General

Color Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles OEM Brand Name Style Type UPC Black, White Indoor Dry Unless Protected By Additional Means 20A Triple Gripper Nylon Plug Composite Cord Mounted 3-Pole Hubbell Bryant Internal Cord Clamp Plugs 781786696921



Dimensions

Dimensions Display Size Height Length Width 2.13 in x 2.13 in x 2.86 in Standard Sized 2.86 in 2.13 in 2.13 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Screw Terminals
Current Rating	20 A
Phase	Three Phase
Voltage Rating	3 Phase 480 VAC
Voltage Rating Description	3 Phase 480 VAC

Conductor Related

Cord Type	All Listed Portables
Number Of Wires	4-Wire
Wire Size	#18 AWG to #8 AWG

Certifications and Compliance

Nema Rating	L16-20P
Logistics	
Carton Quantity	10

Product Assets

Catalog Page - Bryant H-9 Catalog page Catalogs - Bryant Full Line Catalog

HUBBELL

A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. BRY-71620NP-SPEC-EN | REV 4/2023

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com