BRYANT[®]

Locking Devices, Bryant Midget Locking, Industrial, Flanged Receptacle, 15A 125V, 2-Pole 2-Wire Non Grounding, ML-1R, Screw Terminal, Black

By Bryant Catalog # 7468N

Locking Devices, Bryant Midget Locking, Industrial, Flanged Receptacle, 15A 125V, 2-Pole 2-Wire Non Grounding, ML-1R, Screw Terminal, Black

> Indoor Dry Unless Protected By Additional Means

15A Midget Flanged

Receptacle

Composite

2-Pole

Screw Mounting

Hubbell Bryant

Non-Grounding

781786638525

Flanged Receptacle

Application

Extra Heavy Duty Industrial Specification Grade

General

Environmental Conditions

Item Type

Material Material - Mounting Hardware Number Of Poles OEM Brand Name Style Type UPC

Dimensions

Dimensions1.63 in x 1.38 in x 1.18 inDisplay SizeMidget LockingHeight1.18 inLength1.63 inWidth1.38 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current Rating	15 A
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125V



Conductor Related

Certifications and Compliance		
Wire Size	#18 AWG to #12 AWG	
Number Of Wires	2-Wire	

Nema Rating	ML-1R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant H-4 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

7465NB - Locking Devices, Bryant Midget Locking, Industrial, Male Plug, 15A 125V, 2-Pole 2-Wire Non-Grounding, ML-1P, Screw Terminal, Black

7465N - Locking Devices, Bryant Midget Locking, Industrial, Male Plug, 15A 125V, 2-Pole 2-Wire Non-Grounding, ML-1P, Screw Terminal, Black & White

7466N - Locking Devices, Bryant Midget Locking, Industrial, Flanged Inlet, 15A 125V, 2-Pole 2-Wire Non Grounding, ML-1P, Screw Terminal, Black

HUBBELL A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. BRY-7468N-SPEC-EN | REV 7/2023