

Straight Blade Devices

Hospital Grade ● Impact Resistant Plugs and Connectors



- Impact-resistant thermoplastic construction with automatic cord grip
- Transparent polycarbonate cover allows visual inspection of wire terminations without disassembly
- Pre-attached TPE (thermoplastic elastomer) dust seal helps prevent contaminants from entering wiring chamber
- Single side terminal screws reduce wiring time and are color coded for proper terminations

Angled Plugs

All Bryant angle devices are ideally suited for any location where space restrictions or obstructions require the power cord to lay close to the wall or flat against the floor.

Bryant hospital grade transparent angle plugs are designed for straight blade applications in hospitals, as well as industrial, commercial and institutional environments – wherever attachment plugs must withstand severe abuse.

15A and 20A 125V and 20A 250V Plugs and Connectors, 2-Pole 3-Wire Inches (mm)



BRY8266NP



8266T



8295T



BRY8269NC




8269T


Device Type		Straight Plug		Angled Plug	Connector	
Rating	Cord Diameter	White Thermoplastic	Transparent Nylon/Polycarbonate	Transparent Nylon/Polycarbonate	White Thermoplastic	Transparent Nylon/Polycarbonate
NEMA 5-15, 15A 125V 	.245"-.655" (6.2-16.6)	BRY8266NP	8266T	8295T	BRY8269NC	8269T
NEMA 5-20, 20A 125V 	.245"-.655" (6.2-16.6)	BRY8366NP	8366T	8395T	BRY8369NC	8369T
NEMA 6-20, 20A 250V 	.300"-.625" (7.6-15.9)	BRY8466NP	—	8495T	BRY8469NC	—

Product Dimensions Inches (mm)


	Plug	Angled Plug	Connector
A	1.52" (38.6)	1.30" (33.0)	1.52" (38.6)
B	2.18" (55.4)	2.07" (52.6)	2.95" (74.9)
C	1.38" (35.1)	1.52" (38.6)	1.38" (35.1)



Plug



Angled Plug



Connector

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com