



**finder**<sup>®</sup>

SWITCH TO THE FUTURE

**56**  
SERIES

# Miniature power relays 12 A



Industrial  
furnaces and  
ovens



Control and  
management of  
electric power



Industrial  
motors



Circuit breakers  
and switches



Panels for  
electrical  
distribution



Control panels



Carousel  
warehouses



Vending  
machines



### Plug-in - 12 A Power relay, 2 & 4 pole

- Flange mount option - (Faston 187, 4.8 x 0.5 mm termination)
- AC coils & DC coils
- Lockable test button and mechanical flag indicator
- Cadmium Free contacts (standard version)
- Contact material options
- 96 series sockets
- Coil EMC suppression
- Accessories
- European Patent

### 56.32/56.34









- 2 or 4 pole changeover contact
- Plug-in/Faston 187

### 56.32-0300



- 2 pole normally open contact ( $\geq 1.5$  mm gap)
- Plug-in/Faston 187



56.32

56.34

56.32-0300

\* For 4 CO (4PDT) only.

For UL RATINGS SEE:

"General technical information" page V

For outline drawing see page 8

### Contact specification

| Contact configuration                   |           | 2 CO (DPDT) | 4 CO (4PDT) | 2NO (DPST-NO) - $\geq 1.5$ mm gap |
|-----------------------------------------|-----------|-------------|-------------|-----------------------------------|
| Rated current/Maximum peak current      | A         | 12/20       |             | 12/20                             |
| Rated voltage/Maximum switching voltage | V AC      | 250/400     |             | 250/400                           |
| Rated load AC1                          | VA        | 3000        |             | 3000                              |
| Rated load AC15 (230 V AC)              | VA        | 700         |             | 700                               |
| Single phase motor rating (230 V AC)    | kW        | 0.55        |             | 0.55                              |
| Breaking capacity DC1: 30/110/220 V     | A         | 12/0.5/0.25 |             | 12/1/0.5                          |
| Minimum switching load                  | mW (V/mA) | 500 (10/5)  |             | 500 (10/5)                        |
| Standard contact material               |           | AgNi        |             | AgNi                              |

### Coil specification

|                           |                 |                                                      |                       |                        |
|---------------------------|-----------------|------------------------------------------------------|-----------------------|------------------------|
| Nominal voltage ( $U_N$ ) | V AC (50/60 Hz) | 6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400* |                       |                        |
|                           | V DC            | 6 - 12 - 24 - 48 - 60 - 110 - 125 - 220              |                       | —                      |
| Rated power AC/DC         | VA (50 Hz)/W    | 1.5/1                                                | 2/1.3                 | 1.5/—                  |
| Operating range           | AC              | $(0.8 \dots 1.1) U_N$                                |                       | $(0.85 \dots 1.1) U_N$ |
|                           | DC              | $(0.8 \dots 1.1) U_N$                                | $(0.8 \dots 1.1) U_N$ | —                      |
| Holding voltage           | AC/DC           | 0.8 $U_N$ / 0.6 $U_N$                                |                       | 0.85 $U_N$ / —         |
| Must drop-out voltage     | AC/DC           | 0.2 $U_N$ / 0.1 $U_N$                                |                       | 0.2 $U_N$ / —          |

### Technical data

|                                                       |        |                                             |       |                          |
|-------------------------------------------------------|--------|---------------------------------------------|-------|--------------------------|
| Mechanical life AC/DC                                 | cycles | 20 · 10 <sup>6</sup> / 50 · 10 <sup>6</sup> |       | 20 · 10 <sup>6</sup> / — |
| Electrical life at rated load AC1                     | cycles | 100 · 10 <sup>3</sup>                       |       | 100 · 10 <sup>3</sup>    |
| Operate/release time                                  | ms     | 9/6                                         | 11/11 | 8/4                      |
| Insulation between coil and contacts (1.2/50 $\mu$ s) | kV     | 4                                           | 5     | 4                        |
| Dielectric strength between open contacts             | V AC   | 1000                                        |       | 2000                     |
| Ambient temperature range                             | °C     | -40...+70                                   |       | -40...+70                |
| Environmental protection                              |        | RT I                                        |       | RT I                     |

Approvals (according to type)



## Printed circuit mount


## 12 A Power relay

- 2 & 4 pole
- AC coils & DC coils
- Cadmium Free contacts (standard version)
- Contact material option

## 56.42/56.44




- 2 or 4 pole changeover contact
- PCB mount

56.42  
Copper side view56.44  
Copper side view

## 56.42-0300



- 2 pole normally open contact ( $\geq 1.5$  mm gap)
- PCB mount

56.42-0300  
Copper side view

\* For 4 CO (4PDT) only.

FOR UL RATINGS SEE:

"General technical information" page V

For outline drawing see page 8

## Contact specification

| Contact configuration                       |           | 2 CO (DPDT) | 4 CO (4PDT) | 2NO (DPST-NO) - $\geq 1.5$ mm gap |
|---------------------------------------------|-----------|-------------|-------------|-----------------------------------|
| Rated current/Maximum peak current          | A         | 12/20       |             | 12/20                             |
| Rated voltage/<br>Maximum switching voltage | V AC      | 250/400     |             | 250/400                           |
| Rated load AC1                              | VA        | 3000        |             | 3000                              |
| Rated load AC15 (230 V AC)                  | VA        | 700         |             | 700                               |
| Single phase motor rating (230 V AC)        | kW        | 0.55        |             | 0.55                              |
| Breaking capacity DC1: 30/110/220 V         | A         | 12/0.5/0.25 |             | 12/1/0.5                          |
| Minimum switching load                      | mW (V/mA) | 500 (10/5)  |             | 500 (10/5)                        |
| Standard contact material                   |           | AgNi        |             | AgNi                              |

## Coil specification

|                           |                 |                                                      |                       |                        |
|---------------------------|-----------------|------------------------------------------------------|-----------------------|------------------------|
| Nominal voltage ( $U_N$ ) | V AC (50/60 Hz) | 6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400* |                       |                        |
|                           | V DC            | 6 - 12 - 24 - 48 - 60 - 110 - 125 - 220              |                       |                        |
| Rated power AC/DC         | VA (50 Hz)/W    | 1.5/1                                                | 2/1.3                 | 1.5/—                  |
| Operating range           | AC              | $(0.8 \dots 1.1) U_N$                                |                       | $(0.85 \dots 1.1) U_N$ |
|                           | DC              | $(0.8 \dots 1.1) U_N$                                | $(0.8 \dots 1.1) U_N$ | —                      |
| Holding voltage           | AC/DC           | $0.8 U_N / 0.6 U_N$                                  |                       | $0.85 U_N / —$         |
| Must drop-out voltage     | AC/DC           | $0.2 U_N / 0.1 U_N$                                  |                       | $0.2 U_N / —$          |

## Technical data

|                                                            |        |                                 |       |                     |
|------------------------------------------------------------|--------|---------------------------------|-------|---------------------|
| Mechanical life AC/DC                                      | cycles | $20 \cdot 10^6 / 50 \cdot 10^6$ |       | $20 \cdot 10^6 / —$ |
| Electrical life at rated load AC1                          | cycles | $100 \cdot 10^3$                |       | $100 \cdot 10^3$    |
| Operate/release time                                       | ms     | 9/6                             | 11/11 | 8/4                 |
| Insulation between coil<br>and contacts ( $1.2/50 \mu s$ ) | kV     | 4                               | 5     | 4                   |
| Dielectric strength<br>between open contacts               | V AC   | 1000                            |       | 2000                |
| Ambient temperature range                                  | °C     | -40...+70                       |       | -40...+70           |
| Environmental protection                                   |        | RT I                            |       | RT I                |

## Approvals (according to type)



## Ordering information

Example: 56 series plug-in relay, 2 CO (DPDT), 12 V DC coil, lockable test button and mechanical indicator.

|                                                                                                                 | 5 | 6 | . | 3 | . | 2 | . | 9 | . | 0 | 1 | 2 | . | 0 | A | 0 | B | 0 | C | 4 | D | 0 |
|-----------------------------------------------------------------------------------------------------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| <b>Series</b>                                                                                                   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>Type</b>                                                                                                     |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 3 = Plug-in                                                                                                     |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 4 = PCB                                                                                                         |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>No. of poles</b>                                                                                             |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 2 = 2 pole, 12 A                                                                                                |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 4 = 4 pole, 12 A                                                                                                |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>Coil version</b>                                                                                             |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 8 = AC (50/60 Hz)                                                                                               |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 9 = DC                                                                                                          |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>Coil voltage</b>                                                                                             |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| See coil specifications                                                                                         |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>A: Contact material</b>                                                                                      |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 0 = Standard AgNi                                                                                               |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 2 = AgCdO                                                                                                       |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 4 = AgSnO <sub>2</sub>                                                                                          |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>B: Contact circuit</b>                                                                                       |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 0 = CO (nPDT)                                                                                                   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 3 = NO (nPST), ≥ 1.5 mm contact gap                                                                             |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>D: Special versions</b>                                                                                      |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 0 = Standard                                                                                                    |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 6 = Rear flange mount (4 pole only)                                                                             |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 8 = Rear 35 mm rail mount (4 pole only)                                                                         |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| For other mounting options see page 9                                                                           |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| <b>C: Options</b>                                                                                               |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 0 = None                                                                                                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 2 = Mechanical indicator                                                                                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 3* = LED (AC)                                                                                                   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 4 = Lockable test button + mechanical indicator                                                                 |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 5* = Lockable test button + LED (AC)                                                                            |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 54* = Lockable test button + LED (AC) + mechanical indicator                                                    |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 6* = Double LED (DC non-polarized)                                                                              |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 7* = Lockable test button + double LED (DC non-polarized)                                                       |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 74* = Lockable test button + double LED (DC non-polarized) + mechanical indicator                               |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 8* = LED + diode (DC, polarity positive to pin 7) for 56.32 only                                                |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 9* = Lockable test button + LED + diode (DC, polarity positive to pin 7) for 56.32 only                         |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| 94* = Lockable test button + LED + diode (DC, polarity positive to pin 7) + mechanical indicator for 56.32 only |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| * Options not available for 220 V DC and 400 V AC versions.                                                     |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |


### Selecting features and options: only combinations in the same row are possible.

Preferred selections for best availability are shown in **bold**.

| Type  | Coil version | A                | B        | C                                | D                |
|-------|--------------|------------------|----------|----------------------------------|------------------|
| 56.32 | AC           | <b>0</b> - 2 - 4 | <b>0</b> | 0 - 2 - 3 - <b>4</b> - 5         | <b>0</b>         |
|       | AC           | 0 - 2 - 4        | 0        | 54                               | /                |
|       | AC           | 0 - 2 - 4        | 3        | 0 - 3 - 5                        | 0                |
|       | DC           | <b>0</b> - 2 - 4 | <b>0</b> | 0 - 2 - <b>4</b> - 6 - 7 - 8 - 9 | <b>0</b>         |
|       | DC           | 0 - 2 - 4        | 0        | <b>74</b> - <b>94</b>            | /                |
| 56.34 | AC           | <b>0</b> - 2 - 4 | <b>0</b> | <b>0</b> - 2 - 3 - <b>4</b> - 5  | <b>0</b> - 6 - 8 |
|       | AC           | 0 - 2 - 4        | 0        | 54                               | /                |
|       | DC           | <b>0</b> - 2 - 4 | <b>0</b> | <b>0</b> - 2 - <b>4</b> - 6 - 7  | <b>0</b> - 6 - 8 |
|       | DC           | 0 - 2 - 4        | <b>0</b> | <b>74</b>                        | /                |
| 56.42 | DC           | <b>0</b> - 2 - 4 | <b>0</b> | <b>0</b>                         | <b>0</b>         |
|       | AC           | 0 - 2 - 4        | 0 - 3    | 0                                | 0                |
| 56.44 | AC - DC      | <b>0</b> - 2 - 4 | <b>0</b> | <b>0</b>                         | <b>0</b>         |

### Special versions for Rail Applications on request


### Descriptions: options and special versions



**C: Option 3, 5, 54**  
LED (AC)

**C: Option 6, 7, 74**  
Double LED  
(DC non-polarized)

**C: Option 8, 9, 94**  
LED + diode (DC, polarity  
positive to pin 7) -  
(56.32 only)



### Lockable test button and mechanical flag indicator (0040, 0050, 0054, 0070, 0074, 0090, 0094)

The dual-purpose Finder test button can be used in two ways:

**Case 1)** The plastic pip (located directly above the test button) remains intact. In this case, when the test button is pushed, the contacts operate. When the test button is released the contacts return to their former state.

**Case 2)** The plastic pip is broken-off (using an appropriate cutting tool). In this case, (in addition to the above function), when the test button is pushed and rotated, the contacts are latched in the operating state, and remain so until the test button is rotated back to its former position.

In both cases ensure that the test button actuation is swift and decisive.

## Technical data

\* Only in applications where over voltage category II is permitted. In applications of over voltage category III: Micro-disconnection.


A

| Insulation according to EN 61810-1                                          |                         | 2 CO - 4 CO             |                    | 2 NO                |                    |
|-----------------------------------------------------------------------------|-------------------------|-------------------------|--------------------|---------------------|--------------------|
| Nominal voltage of supply system                                            | V AC                    | 230/400                 |                    | 230/400             |                    |
| Rated insulation voltage                                                    | V AC                    | 250                     | 400                | 250                 | 400                |
| Pollution degree                                                            |                         | 3                       | 2                  | 3                   | 2                  |
| Insulation between coil and contact set                                     |                         |                         |                    |                     |                    |
| Type of Insulation                                                          |                         | Basic                   |                    | Basic               |                    |
| Overvoltage category                                                        |                         | III                     |                    | III                 |                    |
| Rated impulse voltage                                                       | kV (1.2/50 μs)          | 4                       |                    | 4                   |                    |
| Dielectric strength                                                         | V AC                    | 2500                    |                    | 2500                |                    |
| Insulation between adjacent contacts                                        |                         |                         |                    |                     |                    |
| Type of insulation                                                          |                         | Basic                   |                    | Basic               |                    |
| Overvoltage category                                                        |                         | III                     |                    | III                 |                    |
| Rated impulse voltage                                                       | kV (1.2/50 μs)          | 4                       |                    | 4                   |                    |
| Dielectric strength                                                         | V AC                    | 2500                    |                    | 2500                |                    |
| Insulation between open contacts                                            |                         |                         |                    |                     |                    |
| Type of disconnection                                                       |                         | Micro-disconnection     |                    | Full-disconnection* |                    |
| Overvoltage category                                                        |                         | —                       |                    | II                  |                    |
| Rated impulse voltage                                                       | kV (1.2/50 μs)          | —                       |                    | 2.5                 |                    |
| Dielectric strength                                                         | V AC/kV (1.2/50 μs)     | 1000/1.5                |                    | 2000/3              |                    |
| Insulation between coil terminals                                           |                         |                         |                    |                     |                    |
| Rated impulse voltage (surge) differential mode (according to EN 61000-4-5) | kV(1.2/50 μs)           | 4                       |                    |                     |                    |
| Other data                                                                  |                         |                         |                    |                     |                    |
| Bounce time: NO/NC                                                          | ms                      | 1/4 (2 CO) , 1/7 (4 CO) |                    | 3/— (normally open) |                    |
| Vibration resistance (5...55)Hz: NO/NC                                      | g                       | 17/14                   |                    |                     |                    |
| Shock resistance                                                            | g                       | 20/14                   |                    |                     |                    |
| Power lost to the environment                                               | without contact current | W                       | 1 (56.32, 56.42)   |                     | 1.3 (56.34, 56.44) |
|                                                                             | with rated current      | W                       | 3.8 (56.32, 56.42) |                     | 6.9 (56.34, 56.44) |
| Recommended distance between relays mounted on PCB                          |                         | mm                      | ≥ 5                |                     |                    |

## Contact specification


## F 56 - Electrical life (AC) v contact current

2 - 4 pole relays




## H 56 - Maximum DC1 breaking capacity

Changeover version



## H 56 - Maximum DC1 breaking capacity

Normally open version



- When switching a resistive load (DC1) having voltage and current values under the curve, an electrical life of  $\geq 100 \cdot 10^3$  can be expected.
- In the case of DC13 loads, the connection of a diode in parallel with the load will permit a similar electrical life as for a DC1 load.

Note: the release time of the load will be increased.

## Coil specifications


**DC coil data, 2 pole relay**

| Nominal voltage<br>$U_N$ | Coil code | Operating range |           | Resistance<br>$R$ | Rated coil consumption<br>$I$ at $U_N$ |
|--------------------------|-----------|-----------------|-----------|-------------------|----------------------------------------|
| V                        |           | $U_{min}$       | $U_{max}$ | $\Omega$          | mA                                     |
| 6                        | 9.006     | 4.8             | 6.6       | 40                | 150                                    |
| 12                       | 9.012     | 9.6             | 13.2      | 140               | 86                                     |
| 24                       | 9.024     | 19.2            | 26.4      | 600               | 40                                     |
| 48                       | 9.048     | 38.4            | 52.8      | 2400              | 20                                     |
| 60                       | 9.060     | 48              | 66        | 4000              | 15                                     |
| 110                      | 9.110     | 88              | 121       | 12500             | 8.8                                    |
| 125                      | 9.125     | 100             | 138       | 17300             | 7.2                                    |
| 220                      | 9.220     | 176             | 242       | 54000             | 4                                      |

**DC coil data, 4 pole relay**

| Nominal voltage<br>$U_N$ | Coil code | Operating range |           | Resistance<br>$R$ | Rated coil consumption<br>$I$ at $U_N$ |
|--------------------------|-----------|-----------------|-----------|-------------------|----------------------------------------|
| V                        |           | $U_{min}$       | $U_{max}$ | $\Omega$          | mA                                     |
| 6                        | 9.006     | 4.8             | 6.6       | 32.5              | 185                                    |
| 12                       | 9.012     | 9.6             | 13.2      | 123               | 97                                     |
| 24                       | 9.024     | 19.2            | 26.4      | 490               | 49                                     |
| 48                       | 9.048     | 38.4            | 52.8      | 1800              | 27                                     |
| 60                       | 9.060     | 48              | 66        | 3000              | 20                                     |
| 110                      | 9.110     | 88              | 121       | 10400             | 10.5                                   |
| 125                      | 9.125     | 100             | 138       | 14200             | 8.8                                    |
| 220                      | 9.220     | 176             | 242       | 44000             | 5                                      |

**R 56 - DC coil operating range v ambient temperature**  
2 and 4 pole relay



- 1 - Max. permitted coil voltage.  
2 - Min. pick-up voltage with coil at ambient temperature.

**AC coil data, 2 pole relay**


| Nominal voltage<br>$U_N$ | Coil code | Operating range |           | Resistance<br>$R$ | Rated coil consumption<br>$I$ at $U_N$ (50 Hz) |
|--------------------------|-----------|-----------------|-----------|-------------------|------------------------------------------------|
| V                        |           | $U_{min}^*$     | $U_{max}$ | $\Omega$          | mA                                             |
| 6                        | 8.006     | 4.8             | 6.6       | 12                | 200                                            |
| 12                       | 8.012     | 9.6             | 13.2      | 50                | 97                                             |
| 24                       | 8.024     | 19.2            | 26.4      | 190               | 53                                             |
| 48                       | 8.048     | 38.4            | 52.8      | 770               | 25                                             |
| 60                       | 8.060     | 48              | 66        | 1200              | 21                                             |
| 110                      | 8.110     | 88              | 121       | 3940              | 12.5                                           |
| 120                      | 8.120     | 96              | 132       | 4700              | 12                                             |
| 230                      | 8.230     | 184             | 253       | 17000             | 6                                              |
| 240                      | 8.240     | 192             | 264       | 19100             | 5.3                                            |

\*  $U_{min} = 0.85 U_N$  for normally open version.


**AC coil data, 4 pole relay**

| Nominal voltage<br>$U_N$ | Coil code | Operating range |           | Resistance<br>$R$ | Rated coil consumption<br>$I$ at $U_N$ (50 Hz) |
|--------------------------|-----------|-----------------|-----------|-------------------|------------------------------------------------|
| V                        |           | $U_{min}$       | $U_{max}$ | $\Omega$          | mA                                             |
| 6                        | 8.006     | 4.8             | 6.6       | 5.7               | 300                                            |
| 12                       | 8.012     | 9.6             | 13.2      | 22                | 150                                            |
| 24                       | 8.024     | 19.2            | 26.4      | 81                | 90                                             |
| 48                       | 8.048     | 38.4            | 52.8      | 380               | 37                                             |
| 60                       | 8.060     | 48              | 66        | 600               | 30                                             |
| 110                      | 8.110     | 88              | 121       | 1900              | 16.5                                           |
| 120                      | 8.120     | 96              | 132       | 2560              | 13.4                                           |
| 230                      | 8.230     | 184             | 253       | 7700              | 9                                              |
| 240                      | 8.240     | 192             | 264       | 10000             | 7.5                                            |
| 400                      | 8.400     | 320             | 440       | 26000             | 4.9                                            |

**R 56 - AC coil operating range v ambient temperature**  
2 pole relay




**R 56 - AC coil operating range v ambient temperature**  
4 pole relay




- 1 - Max. permitted coil voltage.  
2 - Min. pick-up voltage with coil at ambient temperature.

## Outline drawings


Types 56.32/32-0300




Type 56.34



Types 56.42/42-0300



Type 56.44





## Accessories




**056.25**




**056.25 with relay**

**Top flange mount adaptor for 56.32**

**056.25**



**056.25**



**056.25 with relay**




**056.26**




**056.26 with relay**

**Rear flange mount adaptor for 56.32**

**056.26**



**056.26**



**056.26 with relay**




**056.27**




**056.27 with relay**

**Top 35 mm rail (EN 60715) adaptor for 56.32**

**056.27**



**056.27**



**056.27 with relay**




**056.45**




**056.45 with relay**

**Top flange mount adaptor for 56.34**

**056.45**



**056.45**



**056.45 with relay**




**056.47**




**056.47 with relay**

**Top 35 mm rail (EN 60715) adaptor for 56.34**


**056.47**



**056.47**



**056.47 with relay**



**060.48**

**Sheet of marker tags** for relay type 56.34, plastic, 48 tags, 6 x 12 mm, for CEMBRE thermal transfer printers

**060.48**