

# OTM

## Fast-Acting Midget Fuses

### MIDGET, PC MOUNT & MINIATURE FUSES

M  
F



One-time OTM midget fuses provide low-cost protection for 250 volt AC general purpose lighting, heating, control circuits, etc. where time-delay is not required. (Not for Branch Circuit Protection).

### FEATURES/BENEFITS:

- Low cost and fully rated for economy without compromise
- Can be used with UltraSafe™ fuse holders
- 1 1/2" x 13/32" (10 mm x 38 mm) dimensions

### CATALOG NUMBERS (AMPS)

|      |      |      |       |       |       |
|------|------|------|-------|-------|-------|
| OTM1 | OTM3 | OTM5 | OTM8  | OTM15 | OTM25 |
| OTM2 | OTM4 | OTM6 | OTM10 | OTM20 | OTM30 |

### RECOMMENDED FUSE BLOCKS for Midget (10x38mm) Fuses

| Number of Poles | UltraSafe™ Indicating Fuse Holder | Catalog Number  |                          |                      |
|-----------------|-----------------------------------|-----------------|--------------------------|----------------------|
|                 |                                   | Screw Connector | Pressure Plate Connector | Copper Box Connector |
| Adder           |                                   | 30310           | 30320                    | 30350                |
| 1               | USM1I                             | 30311           | 30321                    | 30351                |
| 2               | USM2I                             | 30312           | 30322                    | 30352                |
| 3               | USM3I                             | 30313           | 30323                    | 30353                |
| 3               | USFM10I                           |                 |                          |                      |

### RATINGS:

- **Volts:** 250VAC
- **Amps:** 1 to 30A
- **I.R.:** 10kA I.R.

### HIGHLIGHTS:

- Fast-acting

### APPLICATIONS:

- Supplemental protection of circuits up to 250VAC and 10kA

### APPROVALS:

- UL Listed to standard 248-14, File E33925
- CSA Certified to Standard C22.2 No. 248.14

