

UL 508 Non-Fusible

Disconnect Switches

DISCONNECT SWITCHES

M163 – M803



The M-series Load Break Switch is the most compact industrial-grade switch on the market. Capable of making or breaking loads up to 600V (UL), it is suitable as a motor disconnect. Extremely compact and robust, these switches have a variety of mounting options including DIN-rail, base, or door-mounting. A wide assortment of handles, shafts and accessories is available to accommodate any installation requirement.

APPLICATIONS:

- Line-of-sight disconnect
- Electrical isolation
- Branch-circuit switch
- Motor disconnect

RATINGS (UL):

- **Volts:** 600VAC
- **Amps:** 20, 30, 40, 63, and 80A. Suitable as motor disconnect up to 40hp.

FEATURES/ BENEFITS:

- Compact
- Robust
- DIN-rail, base, or door mounting
- Choice of handles and shafts
- Padlockable
- Side-mount auxiliary contacts and additional poles
- Double-break, silver-plated, contacts

APPROVALS:














- UL 508 listed E196672
- IEC 60947-3



Catalog number designation

M Switch	80 Ampacity	3 Number of Poles	Special Configurations
M = Mersen AC Switch	16-80		DM: Door Mounting

UL 508 Disconnect Switches—Front Operated

						
M163	M163DM	M633	M633DM			
Switch Body	Ampere Rating	20	30	40	63	80
	Base Part #	M163	M253	M403	M633	M803
	Door-Mounted Version	M163DM	M253DM	M403DM	M633DM	M803DM
Handles and Shafts	Direct Front Operation Locking Handle					
 HD40  HB65  SA105  SPA130		HD40	HD40	HD40	HD125	HD125
	External Front Operation					
	Selector Style NEMA Type 1, 3R, 12	HSBX, HSRX				
	Shaft—SAxxx (xxx = length in mm)	SA85, SA105, SA120, SA130, SA180, SA250				
	Door mounted version (no shaft required)	HSBPDM, HSRPDM		HSBWDM, HSRWDM		
	Pistol Style NEMA Type 1, 3R, 12	HB45, HR45, HB65, HR65, HB80, HR80				
	NEMA Type 4, 4X	HB45X, HR45X, HB65X, HR65X, HB80, HB80X				
	NEMA 4X Stainless Steel	HM65X				
	Shaft— SAxxx (xxx = length in mm)	SPA130, SPA210, SPA290, SPA360, SPA430				
	B=Black, R=Black					
Accessories	Fourth Poles					
 4P40  4P80	Limited to one additional pole per switch	4P40	4P40	4P40	4P80	4P80
	Door mounted switch 4th poles are left-side mounted	4P40DM	4P40DM	4P40DM	4P80DM	4P80DM
 OA1G10  OA2G11  OA1G01	Neutral Poles					
	Limited to one additional pole per switch	NP40	NP40	NP40	NP80	NP80
	Door mounted switch neutral poles	NP40DM	NP40DM	NP40DM	NP80DM	NP80DM
	Terminal Shrouds					
	3-pole	TS40-3	TS40-3	TS40-3	TS63-3	TS63-3
	4-pole (Add this to the 3-pole shroud)	TS40-1	TS40-1	TS40-1	TS63-1	TS63-1
	Auxiliary Contacts*					
	NC Right side mounting	OA1G01	OA1G01	OA1G01	OA1G01	OA1G01
	NO left side mounting	OA1G10	OA1G10	OA1G10	OA1G10	OA1G10
	NO+NC (Mounting on either side)	OA2G11	OA2G11	OA2G11	OA2G11	OA2G11
*Rated 2A max continous @690VAC						

TECHNICAL DATA ACCORDING TO UL/cULus															
Part Number	pf= 0.7...0.8	-40° to 40 °C	A		M163		M253		M403		M633		M803		
General Purpose Amp Rating					20		30		40		60		80		
Maximum Operating Voltage			V		600		600		600		600		600		
Max. horsepower rating / motor FLA current	pf= 0.4...0.5 Three phase	240 V	HP/A		5/15.2		7.5/22.0		10/28.0		15/42.0		20/54.0		
		480 V	HP/A		10/14.0		15/21.0		20/27.0		30/40.0		40/52.0		
		600 V	HP/A		11-Oct		20/22.0		25/27.0		30/32.0		40/41.0		
	Single phase	120 V	HP/A		1/16.0		1.5/20.0		2/24.0		2/24.0		2/24.0		
		240 V	HP/A		2/13.2		3/18.7		5/30.8		7.5/40.0		10/57.5		
Short circuit rating with fuse	Maximum fuse size		A		30	60 ²⁾	30	60 ²⁾	30	60 ²⁾	100	150	100	150	
	Fuse type	CC	kA		10		10		10						
	Fuse type	J	kA		10	10	10	10	10	10	100		100		
	Fuse type	T	kA		10	10	10	10	10	10	100		100		
	Fuse type	RK1	kA		10		10		10		10	5	10	5	
	Fuse type	RK5	kA		5	5	5	5	5	5		5		5	
	Fuse type	L	kA												
	Fuse type	H	kA												
Endurances															
Min. electrical endurance, pf. 0.75...0.8			oper. cycles		6 000		6 000		6 000		6 000		6 000		
Mechanical endurance			operations		20 000		20 000		20 000		20 000		20 000		
Terminal lug kits					Integral		Integral		Integral		Integral		Integral		
Wire range			AWG		18-8		18-8		18-8		14-4		14-4		
Torque		Wire tightening	lb. in		7		7		7		18		18		
		Lug mounting													
TECHNICAL DATA ACCORDING TO IEC 60947-3															
Rated insulation voltage and rated operational voltage AC20/DC20		Pollution degree 3	V		750		750		750		750		750		
Dielectric strength		50 Hz 1min.	kV		6		6		6		6		6		
Rated impulse withstand voltage			kV		8		8		8		8		8		
Rated operational current, AC-22A		up to 415 V	A		16		25		40		63		80		
		440...500 V	A		16		25		40		63		80		
		690 V	A		16		25		40		63		80		
Rated operational current, AC-23A		up to 415 V	A		16		20		23		45		75		
		440 V	A		16		20		23		45		65		
		500 V	A		16		20		23		45		58		
		690 V	A		10		11		12		20		20		
Rated conditional short-circuit current I _p (r.m.s.) and corresponding max. allowed cut-off current i _c . The cut-off current i _c refers to values listed by fuse manufacturers	I _p (r.m.s.)	50 kA	kA		6.5		6.5		6.5		13		13		
	Max. fuse size gG/aM	415 V	A		40/32		40/32		40/32		100/80		100/80		
	I _p (r.m.s.)	10 kA	kA												
	Max. fuse size gG/aM	690 V	A												
(single phase test acc. to IEC60269)	I _p (r.m.s.)	50 kA	kA		4		4		4		11		11		
	Max. fuse size gG/aM	690 V	A		25/16		25/16		25/16		80/63		80/63		
	at prospective SC-current	80 kA	kA												
	Max. fuse size gG/aM	690 V	A												
Rated short-time withstand current		r.m.s. -value I _{cw}	690 V, 1 s		kA		0.5		0.5		0.5		1		
Rated short circuit making capacity		Peak value I _{cm}	690 V/500 V		A		0.705		0.705		0.705		1.4		
Power loss / pole		At rated operational current		W		0.3		0.6		1.6		2.8		4.5	
Mechanical endurance		Divide by two for operation cycles		Oper.		20 000		20 000		20 000		20 000		20 000	
Weight without accessories		3-pole	kg		0.11		0.11		0.11		0.27		0.27		
		4-pole	kg		0.15		0.15		0.15		0.35		0.35		

1) UL Listed switches are also CSA Approved. 2) Fuse size 70A for RK5.