

## RSRS SERIES STEEL CORD GRIPS



## **RSRS SERIES STEEL CORD CONNECTORS**

The Tuff-Seal<sup>™</sup> RSRS series of corrosion-resistant cord connectors features a body and compression nut made of zinc-chromium plated steel for added strength and durability, enhanced resistance to rust and a better physical appearance. These connectors are ideally suited for use in washdowns or high moisture environments in food processing plants, petrochemical facilities, wastewater treatment plants, pulp & paper mills and chemical manufacturing factories.

RSRS cord connectors have been designed to withstand the extremes of water, caustic materials, detergents or surfactants.

RSRS Corrosion-Resistant Connectors can be ordered with or without wire mesh and accommodate 3/8", 1/2", 3/4" and 1" conduit. The combination tightening surface on these connectors is a unique Remke design that provides a large wrenching area for easy installation. And the knurl section offers users an extra gripping surface for initial hand tightening.

## NOTES

CORD GRIP ACCESSORIES Locknuts: add "-L" to any part number O-Rings: add "-R" to any part number

SPECIAL CONFIGURATIONS Special configurations and materials are available. Consult factory.

All wire mesh is stainless steel

Dimension & certification information on pages 62 & 64 in Tuff-Seal Technical Reference. Dimensions are the same as those for RSR Straight Cord Grips.

## COMPLETE ASSEMBLY PART NUMBERS

Cord

Grip

RSRS-003

**BSBS-004** 

**RSRS-005** 

**RSRS-006** 

**RSRS-007** 

**RSRS-103** 

**RSRS-104** 

**RSRS-105** 

**BSBS-106** 

**RSRS-107** 

**RSRS-108** 

**RSRS-109** 

**RSRS-110** 

**BSBS-208** 

**RSRS-209** 

**RSRS-210** 

**RSRS-211** 

**RSRS-212** 

RSRS-213\*

**RSRS-309** 

**RSRS-310** 

**RSRS-311** 

**RSRS-312** 

RSRS-313

**RSRS-314** 

**RSRS-315** 

**RSRS-316** 

**RSRS-416** 

**RSRS-418** 

**RSRS-420** 

RSRS-422

**RSRS-516** 

**BSBS-518** 

**RSRS-520** 

**RSRS-522** 

Cord Grip With

Mesh

\*\*

RSRS-004-F

RSRS-005-E

RSRS-006-E

RSRS-007-E

\*\*

RSRS-104-E

RSRS-105-E

RSRS-106-E

RSRS-107-E

RSRS-108-E

RSRS-109-E

RSRS-110-E

**BSBS-208-E** 

RSRS-209-E

RSRS-210-E

RSRS-211-E

RSRS-212-E

RSRS-213-E

RSRS-309-E

RSRS-310-E

RSRS-311-E

RSRS-312-E

RSRS-313-F

RSRS-314-E

RSRS-315-E

RSRS-316-E

RSRS-416-E

RSRS-418-E

RSRS-420-E

RSRS-422-E

RSRS-516-E

RSRS-518-F

RSRS-520-E

RSRS-522-E

RSRS SERIES STEEL CORD GRIPS

Cable

Range

.125 – .188

188 - 250

.250 – .312

.312 – .375

.375 - .438

.125 - .188

.188 – .250

.250 – .312

.312 - .375

.375 - .438

.438 - .500

.500 - .562

.562 – .625

438 - 500

.500 - .562

.562 - .625

.562 - .688

.625 - .750

.688 – .812

.500 - .562

.562 - .625

.562 - .688

.625 - .750

688 - 812

.750 – .875

.812 - .938

.875 – 1.000

.950 - 1.050

1.050 - 1.150

1.150 - 1.250

1.250 - 1.375

.950 - 1.050

1.050 - 1.150

1.150 - 1.250

1.250 - 1.375

\*\*Contact Remke for mesh availability of this part number

\*Cable may have to be stripped to pass through the bore of the body

Conduit Size

(NPT)

3/8"

1/2"

3/4"

1"

1 1/4"

1 1/2"



IADE IN			
<b>JSA</b>			
JSA	<b>k</b>		

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

