

Rittal – The System.

Faster – better – everywhere.

► Thermostat Internal Enclosure Thermostat - 3110000

Date : Mar 24 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Thermostat Internal Enclosure Thermostat - 3110000



Product Description

Benefits	Flexible mounting on a vertical or horizontal 35 mm support rail to EN 50 022 snap fastening in the enclosure section or on the mounting plate using the supplied adapter. Time-saving connection technique using a terminal strip with a screw connection from the outside.
Technical specifications	Contact population: Single-pole change-over contact as a quick-break contact Bi-metal controller as a temperature-sensitive element with thermal feedback Permissible contact load: Category 5 – 3 (heating): AC 10 (4) A (inductive load at $\cos \varphi = 0.6$) / category 5- 4 (cooling): AC 5 (4) A (inductive load at $\cos \varphi = 0.6$) / DC = max. 30 W Switching difference: approx. 1 K $\pm$ 0.8 K.
Rated operating voltage	24V - 60V(DC) 24V - 230V 1~
Temperature range	+5°C...+60°C
Dimensions	Height: 71 mm (2.8 ") Width: 71 mm (2.8 ") Depth: 33.5 mm (1.3 ")
Color	RAL 7035
Weight/packaging unit	0.1 kg (0.2 lb.)
Packaging unit	1 pc(s).
EAN	4028177036598

Customs tariff number

90321020

Product description (long)

SK Thermostat enclosure internal thermostat 24-230 V 1~ 24-60
V (DC) Colour RAL 7035 WHD: 71 x 71 x 33.5 mm