

Rittal – The System.

Faster – better – everywhere.

► Roof-mounted fan, roof vent - 3139110

Date : Mar 19 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Roof-mounted fan, roof vent - 3139110



Product Description

Air throughput (unimpeded air flow)	500 m³/h (294.3 cfm)
Unimpeded air flow (without filter mats)	500m³/h / 525m³/h
Unimpeded air flow (with filter mats)	417m³/h / 446m³/h
Rated operating voltage	115V 1~ 50Hz/60Hz
Rated current (max)	At 50 Hz: 0.43 A At 60 Hz: 0.55 A
Miniature circuit-breaker/fuse	6A
Temperature range	Ambient temperature range: -30°C...+55°C Storage: -40°C...+70°C
Dimensions	Height: 133 mm (5.2 ") Width: 400 mm (16 ") Depth: 400 mm (16 ")
Required mounting cut-out	Width: 258 mm (10 ") Depth: 258 mm (10 ")
Installation depth	34.6 mm
Color	RAL 7035
Protection category IP to IEC 60 529	IP 55 including filter mat IP 21 without filter mat
Protection category NEMA:	NEMA 12

Rated power Pel	At 50 Hz: 49 W At 60 Hz: 62 W
Weight/packaging unit	5.16 kg (11.4 lb.)
Diagonal fan	Radial capacitor motor
Supply includes	Complete unit ready for connection including filter mat
Note	The use of temperature controllers or indicators is recommended to ensure the fans are energy efficient
Packaging unit	1 pc(s).
EAN	4028177709164
Customs tariff number	84145915
Product description (long)	SK roof-mounted fan TopTherm 500/525 m³/h 115 V 1~ 50/60 Hz WHD: 400 x 133 x 400 mm