

Rittal – The System.

Faster – better – everywhere.

► TopTherm Filter Fan Units - 3238124

Date : Mar 24 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

TopTherm Filter Fan Units - 3238124



Product Description	
Air throughput with outlet filter, including standard filter mat (quantity x order number, throughput 50/60 Hz)	1 x 3238200: 43 m³/h 2 x 3238200: 46 m³/h
Rated operating voltage	24VDC
Rated current (max)	0.24 A
Miniature circuit-breaker/fuse	2A
Temperature range	Ambient temperature range: -15°C...+55°C Storage: -30°C...+70°C
Dimensions	Height: 148.5 mm (5.8 ") Width: 148.5 mm (5.8 ")
Required mounting cut-out	Height: 124 mm (4.9 ") Width: 124 mm (4.9 ")
Build depth	16 mm (0.63 ")
Installation depth	58.5 mm (2.3 ")
Color	RAL 7035
Protection category IP to IEC 60 529	Protection category IP: IP 54 with standard filter and hose-proof hood: IP 56 with standard filter and additional fine filter mat: IP 54
Protection category NEMA:	Protection category NEMA: NEMA 12 with hose-proof hood: NEMA 3R NEMA 4

	NEMA 4X NEMA 3 with standard filter and hose-proof hood: NEMA 12
Weight/packaging unit	0.54 kg (1.2 lb.)
Diagonal fan	Diagonal DC motor
Supply includes	Complete unit ready for connection including filter mat
Note	Electrical connection of the filter fans 3237.XXX is by means of 2 individual wires at the device for all other filter fans by means of a spring-type terminal.
Packaging unit	1 pc(s).
EAN	4028177651722
Customs tariff number	84145915
Product description (long)	SK fan and filter units TopTherm 55 m³/h 24 V (DC) WHD: 148.5 x 148.5 x 16 mm