## Rittal - The System.

Faster – better – everywhere.

## ■ TopTherm Filter Fan Units - 3240110

Date: Mar 24, 2020



> POWER DISTRIBUTION > CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

**ENCLOSURES** 

## TopTherm Filter Fan Units - 3240110



## **Product Description**

Air throughput (unimpeded air flow): 180 m³/h (105.9 cfm)
Air throughput (unimpeded air flow): 160 m³/h (94.2 cfm)

Air throughput with outlet filter, including standard filter mat (quantity x order number, throughput 50/60 Hz)  $1 \times 3240200: 138/121 \text{ m}^3\text{/h}$  $1 \times 3243200: 165/140 \text{ m}^3\text{/h}$  $2 \times 3240200: 165/140 \text{ m}^3\text{/h}$ 

Rated operating voltage 115V 1~ 50Hz/60Hz

Rated current (max) At 50 Hz: 0.42 A At 60 Hz: 0.38 A

Miniature circuit-breaker/fuse 4A

Temperature range Ambient temperature range: -30°C...+55°C

Storage: -30°C...+70°C

Dimensions Height: 255 mm (10 ")

Width: 255 mm (10 ")

Required mounting cut-out Height: 224 mm (8.8 ")

Width: 224 mm (8.8 ")

Build depth 25 mm (0.98 ")

Installation depth 107 mm (4.2 ")

Color RAL 7035

Protection category IP to IEC 60 529 Protection category IP: IP 54

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

with standard filter and hose-proof hood: IP 56

with standard filter and additional fine filter mat: IP 55

Protection category NEMA: Protection category NEMA: NEMA 12

with hose-proof hood: NEMA 3R

NEMA 4 NEMA 4X NEMA 3

with standard filter and hose-proof hood: NEMA 12

Rated power Pel At 50 Hz: 35 W

At 60 Hz: 34 W

Weight/packaging unit 2.08 kg (4.6 lb.)

Noise pressure level At 50 Hz: 51 dB(A)

At 60 Hz: 46 dB(A)

Diagonal fan Diagonal self-starting shaded pole motor

Supply includes Complete unit ready for connection including filter mat

Note Electrical connection of the filter fans 3237.XXX is by means of 2

individual wires at the device for all other filter fans by means of

a spring-type terminal.

Packaging unit 1 pc(s).

EAN 4028177651951

Customs tariff number 84145915

Product description (long) SK fan and filter units TopTherm 180/160 m³/h 115 V 1~ 50/60

Hz WHD: 255 x 255 x 25 mm