

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW - 3303510

Date : Oct 08 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW - 3303510



Product Description

Total cooling output to DIN EN 14511	L 35 L 35 at 60 Hz: 0.66 kW (2252 BTU) L 35 L 50 at 60 Hz: 0.4 kW (1364 BTU)
Air throughput (unimpeded air flow)	External circuit: 345 m³/h (203.1 cfm) Internal circuit: 280 m³/h (164.8 cfm)
Rated operating voltage	115V 1~ 60Hz
Rated current (max)	5.7 A
Start-up current (max)	11.5 A
Miniature circuit-breaker/fuse	10A
Material	Carbon steel
Temperature range	Ambient temperature range: +10°C...+55°C Setting range: +20°C...+55°C
Dimensions	Height: 550 mm (22 ") Width: 280 mm (11 ") Depth: 210 mm (8.3 ")
Color	RAL 7035
Protection category IP to IEC 60 529	Internal circuit IP 54 External circuit IP 34
Rated Power Pel	L 35 L 35 at 60 Hz: 0.5 kW

	L 35 L 50 at 60 Hz: 0.53 kW
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511	1.4
Temperature control	e-Comfort Controller (factory setting +35°C)
Weight/packaging unit	17 kg (37.5 lb.)
Refrigerant-cooling medium	Refrigerant: R134a Quantity: 170 g (6 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 0.24 t
Supply includes	Drilling template Fasteners Nano-coated condenser Wired ready for connection (plug-in terminal strip)
Note	The technical specifications for the wall-mounted cooling unit 3361.540 are valid with an external transformer connected.
Packaging unit	1 pc(s).
EAN	4028177322837
Customs tariff number	84158200
ETIM 6.0	EC000855
ETIM 5.0	EC000855
eCl@ss 8.0/8.1	27180704
eCl@ss 7.0/7.1	27180704
eCl@ss 6.0/6.1	27180704
eCl@ss 5.1/5.1.4	27180704
Product description (long)	SK cooling unit Blue e wall-mounted 0.66 kW 115 V 1~ 60 Hz Sheet steel WHD: 280 x 550 x 210 mm