

Rittal – The System.

Faster – better – everywhere.

► Hygienic Design HD system enclosure - 4000685

Date : Oct 08 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Hygienic Design HD system enclosure - 4000685



Product Description	
Material	Mounting plate: Carbon steel Housing and door: Stainless steel 1.4301 (AISI 304) Seal: Silicone compliant with FDA Guideline 21 CFR 177.2600 HD lock inserts: Stainless steel 1.4404 (AISI 316L)
Surface finish	Mounting plate: Zinc-plated Housing and door: Brushed grain 400 peak-to-valley height <0.8µm Seal: Blue dyed (RAL 5010)
Protection category IP to IEC 60 529	IP 66
Protection category IP to DIN 40 050-9	IP 59K
Supply includes	Mounting plate Right-hand door catch on single-door enclosures may be swapped to the left Door with fitted seal Enclosure frame with welded-on rear panel base plate
Notes	To achieve protection category IP 66/IP 59K HD versions of the side panel roof and if applicable baying frame must be selected.
Options	HD supporting structure with leveling
Dimensions	Height: 1800 mm (71 ") Width: 600 mm (24 ") Depth: 500 mm (20 ")
Material thickness	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ")

	Mounting plate: 3 mm (0.12 ")
Mounting plate	Height: 1696 mm (67 ") Width: 499 mm (20 ")
Number of doors	1
Packaging unit	1 pc(s).
Weight/packaging unit	89 kg (196.2 lb.)
EAN	4028177693586
Customs tariff number	94032080
ETIM 6.0	EC000261
ETIM 5.0	EC000261
eCl@ss 8.0/8.1	27180101
eCl@ss 7.0/7.1	27180101
eCl@ss 6.0/6.1	27180101
eCl@ss 5.1/5.1.4	27180102