

# Rittal – The System.

Faster – better – everywhere.

## ► TS IT Network/Server Enclosure with vented door, with 482.6 mm (19") mounting angles - 5508110

Date : Oct 13 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: [sales@bolenscontrol.com](mailto:sales@bolenscontrol.com)

# TS IT Network/Server Enclosure with vented door, with 482.6 mm (19") mounting angles - 5508110



Product Description	
Material	Carbon steel Aluminum
Surface finish	Enclosure frame: Dipcoat-primed Doors and roof: Dipcoat-primed powder coated Interior installation: Dipcoat-primed
General color	RAL 7035
Color	Housing frame and panels: RAL7035 Interior installation vent grille at the front: RAL 9005
Supply includes	Supply includes: 50 multi-tooth screws M5 captive nuts M5 conductive (supplied loose) Connection accessories for potential equalization with earthing point (supplied loose) Enclosure frame TS 8 with doors and roof plate IPPC pallet Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Two 482.6 mm (19") mounting sections front and rear variably mounted on support strips with quick-release fasteners Aluminum sheet steel door at the front vented (vented surface area approx. 85% perforated) 180° hinges Spacers height 50 mm to raise the fan cover plate for passive cooling (supplied loose) Supply includes: Roof plate multi-piece removable with side cable entry in the depth and covered cut-out for fan mounting plate Carbon steel door at the rear vertically divided vented (vented

	surface area approx. 85% perforated) 180° hinges
Notes	The door-opening angle may vary depending on site requirements or applications
Base material	Carbon steel
Dimensions	Height: 2000 mm (79 ") Width: 600 mm (24 ") Depth: 1000 mm (39 ")
Installation Dimensions	42 U
Installation height for components	42 U
Door Type	Vented
Load capacity	15000 N
482.6 mm (19") version	Profile rails 482.6 mm (19")
Distance between levels as delivered	745 mm (29 ")
Packaging unit	1 pc(s).
Weight/packaging unit	86.8 kg (191.4 lb.)
EAN	4028177678118
Customs tariff number	94032080
ETIM 6.0	EC002499
ETIM 5.0	EC002499
eCl@ss 8.0/8.1	27180207
eCl@ss 7.0/7.1	27180207
eCl@ss 6.0/6.1	27180207
eCl@ss 5.1/5.1.4	27180201
Product description (long)	DK Network/server enclosure TS IT with 19" mounting angles WHD: 600x2000x1000 mm 42 U Aluminium sheet steel door at the front vented Sheet steel door at the rear vented vertically divided