Rittal – The System.

Faster – better – everywhere.





TS 8018.792

TS 8 Floormount Enclosure

State: 1/26/2022 (Source: rittal website)



ENCLOSURES

OWER DISTRIBUTION

CLIMATE CONTROL

INFRASTRUCTURE

SOFTWARE & SERVICES

TS 8018.792 - TS 8 Floormount Enclosure

Rittal's Floormount TS 8 combines the strength of unibody floormount enclosures with the flexibility of Rittal's revolutionary modular design. With its double door configuration and wide range of accessories, Rittal's Floormount TS 8 is sure to meet your UL Type 12 needs.

Features

Material	Enclosure frame: Carbon steel, 1.5 mm
	Roof: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
	Mounting plate: Carbon steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and base plates: Zinc-plated
Color	RAL 7035
Supply includes	Enclosure frame with door(s)
	Roof plate
	Rear panel, detachable
	4 eyebolts
	Padlock Comfort handle
	Base Plates
	Mounting plate
	12 inch removable floor stands
Dimensions	Width: 1,800 mm
	Height: 1,800 mm
	Depth: 500 mm
	Width: 70.9 "
	Height: 70.9 ~
	Depth: 19.7 "
Weight/packaging unit	254 kg
	560 lb.
Packaging unit	1 Stück

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Approvals

Approvals

UL + C-UL