

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 – TS 8285.500

Date : Nov 13, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 – TS 8285.500



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting plate 2 TS punched rails, 18 x 38 mm
Product modification:	The TS 8 and the SE 8 both come with the new mounting plate of the baying enclosure system VX25. You can download the brochure and CAD drawings.

Base material:	Carbon steel
Product description	
Dimensions:	Height: 1800 mm (71 ") Width: 1200 mm (47 ") Depth: 500 mm (20 ")
Mounting plate:	Height: 1696 mm (67 ") Width: 1099 mm (43 ")
Number of doors:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	173.3 kg (382.1 lb.)
EAN:	4028177250932
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	TS Bayed enclosure system, WHD: 1200x1800x500 mm, Sheet steel, with mounting plate, two doors at the front
Approvals	
Approvals:	Bureau Veritas CCC exception letter DNV-GL Lloyds Register of Shipping RRR UL + C-UL
Certificates:	Certificate of manufacturer according to RMRS IK-Code NA Protection category Protection category IP 55 (CPRI)
Declarations:	Declaration of conformity Manufacturer's declaration

