

Rittal – The System.

Faster – better – everywhere.

TS punched rail, 18 x 38 mm – TS 8612.280

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS punched rail, 18 x 38 mm – TS 8612.280



Product description

Description:	Simply locate and secure with a screw. Location system makes installation and removal easy. Only needs to be secured on one side, but can be secured on both sides if necessary.
Material:	Carbon steel
Supply includes:	Assembly screws
Note:	In enclosures with a mounting plate, two punched rails are already included in the scope of supply.

Product features

Suitable for:	Width/depth: 800 mm
Installation options:	On the vertical TS, SE enclosure section on the outer mounting level On the horizontal TS, SE enclosure section On base configuration rail for CM
Packaging unit:	4 pc(s).
Weight/packaging unit:	3.7 kg (8.1 lb.)
EAN:	4028177213111
Customs tariff number:	73269098
ETIM 6.0:	EC002625

ETIM 5.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	23159101
eCl@ss 6.0/6.1:	23159101
eCl@ss 5.1/5.1.4:	27189232
Product description (long):	TS Punched rail 18 x 38 mm, for W/D: 800 mm
Approvals	
Certificates:	EAC