

Rittal – The System.

Faster – better – everywhere.

► Baying systems TS 8 - 8806500

Date : Mar 30 , 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Baying systems TS 8 - 8806500



Product Description	
Material	Material: Door: Carbon steel 2.0 mm Enclosure frame: Carbon steel 1.5 mm Rear wall: carbon steel 1.5 mm Roof: Carbon steel 1.5 mm Material: Base plates: Carbon steel 1.5 mm Mounting plate: Carbon steel 3.0mm
Surface finish	Surface finish: Door roof and rear panel: Dipcoat-primed powder-coated on the outside textured paint Enclosure frame: Dipcoat-primed Surface finish: Mounting plate and base plates: Zinc-plated
Color	RAL 7035
Protection category IP to IEC 60 529	IP 55
Protection category NEMA:	NEMA 12
IK code	IK09
Supply includes	Supply includes: 4 eyebolts Door(s) Enclosure frame Lock: 3 mm double-bit Rear panel Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Supply includes: 2 TS punched rails 18 x 38 mm Base Plates Mounting plate

	2 support strips fitted in the enclosure depth
Product modification	TS 8 and the SE 8 both come with the new mounting plate of the baying enclosure system VX25. The brochure and the CAD drawings are available for downloading.
Base material	Carbon steel
Dimensions	Height: 2000 mm (79 ") Width: 800 mm (31 ") Depth: 600 mm (24 ")
Mounting plate	Height: 1896 mm (75 ") Width: 699 mm (28 ")
Number of doors	1
2 support strips fitted in the enclosure depth	yes
Packaging unit	1 pc(s).
Weight/packaging unit	130.5 kg (287.7 lb.)
EAN	4028177251038
Customs tariff number	94032080
ETIM 6.0	EC000261
ETIM 5.0	EC000261
eCl@ss 8.0/8.1	27180101
eCl@ss 7.0/7.1	27180101
eCl@ss 6.0/6.1	27180101
eCl@ss 5.1/5.1.4	27180101
Product description (long)	TS Bayed enclosure system WHD: 800x2000x600 mm Sheet steel with mounting plate single door at the front