

Rittal – The System.

Faster – better – everywhere.



TS 8806.580

Baying systems TS 8

State: 1/26/2022 (Source: rittal website)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

TS 8806.580 - Baying systems TS 8 IP 66/NEMA 4

TS 8 baying system, protection category IP 66, NEMA 4, sheet steel, spray-finished.

Features

Material	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish	Enclosure frame, door, roof, base and rear panel: Dipcoat-primed and powder-coated, textured paint Mounting plate: Zinc-plated
Color	RAL 7035
Supply includes	Enclosure frame Door Door catch on right, may be swapped to the left Roof plate Base, solid Rear panel Mounting plate 4 eyebolts Lock: 3 mm double-bit 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Accessory kit for side panels for upgrading to IP 66
Dimensions	Width: 800 mm Height: 2,000 mm Depth: 600 mm Width: 31.5 " Height: 78.7 " Depth: 23.6 "
Mounting plate	Width: 699 mm Height: 1,896 mm Width: 27.5 " Height: 74.6 "

Features

Protection category IP to EN 60529	IP 66
Protection category NEMA	NEMA 4 NEMA 3R
IK code	IK09
Base material	Carbon steel
Weight/packaging unit	124 kg 273.4 lb.
Packaging unit	1 Stück
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas C-UL UL + C-UL
Certificates	IK-Code Protection category
Explanations	Manufacturer's declaration Declaration of conformity Declaration of conformity UK