

Rittal – The System.

Faster – better – everywhere.

► OM adapter with Connection Cables - 9340350

Date : Mar 20 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

OM adapter with Connection Cables - 9340350



Product Description

Material	Fire protection corresponding to UL94-V0 Polyamide (PA 6.6)
Color	Chassis: RAL 7035
Notes	The technical data may vary for UL applications.
Suitable for busbars	10 mm 5 mm
Number of poles	3-pole
For bar systems with center-to-center spacing	60 mm
Dimensions	Height: 208 mm (8.2 ") Width: 45 mm (1.8 ")
Support frame	Height: 170 mm (6.7 ") Width: 45 mm (1.8 ")
Connection cable	Cross-section: AWG 10 Length: 130 mm (5.1 ")
Rated current (max.)	32 A
Number of support rails	1
Height of support rails	10 mm (0.39 ")
Support rail type	TS 45C

Packaging unit	1 pc(s).
Weight/packaging unit	0.3 kg (0.7 lb.)
EAN	4028177525559
Customs tariff number	85369095
Product description (long)	SV OM adaptor 32 A 690 V 3-pole connection cable AWG 10 WH: 45x208 mm support frame support rail TS 45C