

# Rittal – The System.

Faster – better – everywhere.

## ► OM adapter with Connection Cables - 9340380

Date : Oct 13 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: [sales@bolenscontrol.com](mailto:sales@bolenscontrol.com)

# OM adapter with Connection Cables - 9340380



| Product Description                           |                                                                |
|-----------------------------------------------|----------------------------------------------------------------|
| Material                                      | Fire protection corresponding to UL94-V0<br>Polyamide (PA 6.6) |
| Color                                         | Chassis: RAL 7035                                              |
| Notes                                         | The technical data may vary for UL applications.               |
| Suitable for busbars                          | 10 mm<br>5 mm                                                  |
| Number of poles                               | 3-pole                                                         |
| For bar systems with center-to-center spacing | 60 mm                                                          |
| Dimensions                                    | Height: 208 mm (8.2 ")<br>Width: 45 mm (1.8 ")                 |
| Support frame                                 | Height: 170 mm (6.7 ")<br>Width: 45 mm (1.8 ")                 |
| Connection cable                              | Cross-section: AWG 10<br>Length: 130 mm (5.1 ")                |
| Rated current (max.)                          | 32 A                                                           |
| Number of support rails                       | 2                                                              |
| Height of support rails                       | 10 mm (0.39 ")                                                 |
| Support rail type                             | TS 45D<br>TS 45D-V                                             |

|                            |                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------|
| Packaging unit             | 1 pc(s).                                                                                                           |
| Weight/packaging unit      | 0.3 kg (0.7 lb.)                                                                                                   |
| EAN                        | 4028177555440                                                                                                      |
| Customs tariff number      | 85369095                                                                                                           |
| ETIM 6.0                   | EC001531                                                                                                           |
| ETIM 5.0                   | EC001531                                                                                                           |
| eCl@ss 8.0/8.1             | 27370304                                                                                                           |
| eCl@ss 7.0/7.1             | 27370304                                                                                                           |
| eCl@ss 6.0/6.1             | 27370304                                                                                                           |
| eCl@ss 5.1/5.1.4           | 27370302                                                                                                           |
| Product description (long) | SV OM adaptor 32 A 690 V 3-pole connection cable AWG 10<br>WH: 45x208 mm support frame support rail TS 45D TS45D-V |