

Rittal – The System.

Faster – better – everywhere.



SV 9340.720 OM adapter

State: 1/27/2022 (Source: rittal website)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

SV 9340.720 - OM adapter with Connection Cables



Features

Material	Polyamide Fire protection corresponding to UL 94-V0
Color	Chassis: RAL 7035
Length	AWG 8
Rated current max.	40 A
Rated operating voltage	690 V, 3~
For busbar systems with centre-to-centre spacing	60 mm
Connection cables (length)	130 mm 5.12 "
Support rail type	TS 55D
Note	The technical data may vary for UL applications.
Number of poles	3-pole
Dimensions	Width: 55 mm Height: 208 mm Width: 2.17 " Height: 8.19 "
Support rails Qty/height	1 / 10 mm 0.39 "
Suitable for busbars	with cross-section height: 5, 10 mm with cross-section height: 0.2, 0.39 "

Features

Support frame (W x H)	55 mm x 170 mm 2.17 " x 6.69 "
Weight/packaging unit	0.36 kg 0.8 lb.
Packaging unit	1 Stück
ETIM 7.0	EC001531
ECLASS 8.0	27370304

Approvals

Approvals	Lloyds Register of Shipping UL + C-UL
Certificates	EAC
Explanations	Declaration of conformity