

Rittal – The System.

Faster – better – everywhere.



SV 9342.220 Connection Adapters

State: 1/27/2022 (Source: rittal website)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

SV 9342.220 - Connection Adapters

For connecting round conductors or laminated copper bars. For bar systems with 60 mm center-to-center spacing.

Features

Material	Cover: ABS Punched section: Polyamide Fire protection corresponding to UL 94-V0
Color	RAL 7035
Rated current max.	125 A
Rated operating voltage	690 V, 3~
Cable outlet	Top/bottom
For busbar systems with centre-to-centre spacing	60 mm
Note	The technical data may vary for UL applications. UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.
Number of poles	3-pole
Dimensions	Width: 55 mm Height: 210 mm Width: 2.17 " Height: 8.27 "
Clamping area for laminated copper bars (W x H)	10 x 7.8 mm 0.39 x 0.31 "
Connection of round conductors, fine wire with wire end ferrule	10 - 25 mm ²
Connection of round conductors, multi-wire	16 - 35 mm ²
Suitable for busbars	with cross-section height: 5, 10 mm with cross-section height: 0.2, 0.39 "

Features

Weight/packaging unit	0.42 kg 0.9 lb.
Packaging unit	1 Stück
ETIM 7.0	EC001531
ECLASS 8.0	27370304

Approvals

Approvals	C-UL C-UR Lloyds Register of Shipping
Certificates	EAC
Explanations	Declaration of conformity