

Rittal – The System.

Faster – better – everywhere.

► Connection Adapters - 9342250

Date : Oct 14 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Connection Adapters - 9342250



Product Description	
Material	Fire protection corresponding to UL94-V0 Chassis 3439.010: Fiberglass-reinforced thermoplastic polyester (PBT) Chassis: Polyamide (PA 6.6) Cover: ABS
Material	Chassis: Polyamide (PA 6.6)
Color	RAL 7035
Notes	The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050. The technical data may vary for UL applications. UL approval only applies in conjunction with AC application
Suitable for busbars	10 mm (0.39 ") 5 mm (0.2 ")
Number of poles	3-pole
For bar systems with center-to-center spacing	60 mm
Dimensions	Height: 210 mm (8.3 ") Width: 90 mm (3.5 ")
Clamping area for laminated copper bars	Height: 15.5 mm Width: 18.5 mm (0.73 ")
Connection for round conductor cross-sections:	Fine wire with wire end ferrule: 35mm² - 120mm²

	Multi-wire: 35mm ² - 120mm ²
Rated current (max.)	250 A
Cable outlet	Top/bottom
Packaging unit	1 pc(s).
Weight/packaging unit	0.78 kg (1.7 lb.)
EAN	4028177503632
Customs tariff number	85369010
ETIM 6.0	EC001531
ETIM 5.0	EC001531
eCl@ss 8.0/8.1	27370304
eCl@ss 7.0/7.1	27370304
eCl@ss 6.0/6.1	27370304
eCl@ss 5.1/5.1.4	27370302
Product description (long)	SV Connection adaptor 250 A 690 V 3-pole cable outlet top/bottom round conductor connection 35-120 mm ² clamping area WH: 18 5x15 5 mm