

Rittal – The System.

Faster – better – everywhere.



SV 9342.320 Connection Adapters

State: 1/28/2022 (Source: rittal website)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

SV 9342.320 - Connection Adapters

For connecting round conductors or laminated copper bars. For bar systems with 60 mm center-to-center spacing.

Features

Material	Cover: ABS Punched section: Polyamide Fire protection corresponding to UL 94-V0
Color	RAL 7035
Rated current max.	1,600 A
Rated operating voltage	690 V, 3~
Cable outlet	Top/bottom
For busbar systems with centre-to-centre spacing	60 mm
Note	The technical data may vary for UL applications. UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.
Number of poles	3-pole
Dimensions	Width: 255 mm Height: 210 mm Width: 10 " Height: 8.27 "
Suitable for busbars	with cross-section height: 5, 10 mm with cross-section height: 0.2, 0.39 "
Clamping area for laminated copper bars for 5 mm bar thickness, (W x H)	65 x 27 mm 2.56 x 1.06 "
Clamping area for laminated copper bars for 10 mm bar thickness, (W x H)	65 x 22 mm 2.56 x 0.87 "

Features

Weight/packaging unit	2.72 kg 6 lb.
Packaging unit	1 Stück
ETIM 7.0	EC001531
ECLASS 8.0	27370304

Approvals

Approvals	C-UL Lloyds Register of Shipping UL + C-UL
Certificates	EAC
Explanations	Declaration of conformity