

Rittal – The System.

Faster – better – everywhere.

► Circuit-Breaker Component Adaptors 3-pole - 9342550

Date : Mar 20 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Circuit-Breaker Component Adaptors 3-pole - 9342550



Product Description	
Material	Fire protection corresponding to UL94-V0 Polyamide (PA 6.6)
Color	RAL 7035
Supply includes	Sliding Blocks Terminal cover
Notes	The technical data may vary for UL applications. Cable outlet: Switch outlet or as outgoing cable from the switchgear
Suitable for busbars	10 mm 5 mm
Number of poles	3-pole
For bar systems with center-to-center spacing	60 mm
Dimensions	Height: 225 mm (8.9 ") Width: 90 mm (3.5 ")
Clamping area for laminated copper bars	Height: 15.5 mm (0.61 ") Width: 18.5 mm (0.73 ")
Type of connection (electrical)	Box terminal
Connection for round conductor cross-sections	35mm² - 120mm²
Rated current (max.)	125 A

Cable outlet	Bottom
To fit manufacturer (model)	ABB (S1 S2 T1 T1UL T2 T2UL XT1 XT2) Allen Bradley (140-CMN) Eaton (NZM1 NZM1UL BZMB1) GE (FD160) OEZ (BC160N) Schneider Electric (NS80 NSC100 NSE75 NS100) Schrack (MC1) Siemens (3RV1353 3VT1 3VA10 3VA11 3VA51) Terasaki (E125 S125)
Packaging unit	1 pc(s).
Weight/packaging unit	0.82 kg (1.8 lb.)
EAN	4028177525665
Customs tariff number	85369095
Product description (long)	SV Circuit-breaker component adaptor 125 A 690 V 3-pole cable outlet bottom round conductor connection 35-120 mm ² clamping area WH: 18 5x15 5 mm