Rittal - The System.

Faster – better – everywhere.

■ Wallmounted enclosure -8017563

Date: Mar 25, 2020



POWER DISTRIBUTION > CLIMATE CONTROL

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

IT INFRASTRUCTURE

Wallmounted enclosure - 8017563



Product Description

Material Door: Carbon steel all-round foamed-in PU seal

Housing: Carbon steel

Surface finish Mounting plate: Zinc-plated

Housing and door: Dipcoat primed powder-coated on the outside

textured paint

Color RAL 7035

Protection category IP to IEC 60 529 IP 66

Protection category NEMA: NEMA 4

Supply includes: Mounting plate

Housing with door(s) Left hand hinge

Rear wall mounting holes

Supply includes: Quarter turn latch with slotted head insert

Dimensions Height: 760 mm (30 ")

Width: 600 mm (24 ")
Depth: 250 mm (9.8 ")

Material thickness Housing: 1.5 mm (0.06 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate Height: 730 mm (29 ")

Width: 549 mm (22 ")

Packaging unit 1 pc(s).

Weight/packaging unit 34 kg (75 lb.)

EAN 83142