

# Rittal – The System.

Faster – better – everywhere.

## ► Wallmounted enclosure - 1077250

Date : Mar 25 , 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: [sales@bolenscontrol.com](mailto:sales@bolenscontrol.com)

# Wallmounted enclosure - 1077250



Product Description	
Material	Door: Carbon steel all-round foamed-in PU seal Housing: Carbon steel
Surface finish	Mounting plate: Zinc-plated Housing and door: Dipcoat primed powder-coated on the outside textured paint
Color	RAL 7035
Protection category IP to IEC 60 529	IP 66
Protection category NEMA:	NEMA 4
Supply includes	Supply includes: Mounting plate Housing with door(s) Left hand hinge Rear wall mounting holes Supply includes: Quarter turn latch with slotted head insert
Dimensions	Height: 760 mm (30 ") Width: 760 mm (30 ") Depth: 210 mm (8.3 ")
Material thickness	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ") Mounting plate: 2.5 mm (0.1 ")
Mounting plate	Height: 730 mm (29 ") Width: 704 mm (28 ")
Packaging unit	1 pc(s).

Weight/packaging unit	40 kg (88.2 lb.)
EAN	4028177532724