

Product data sheet

Specifications

SQUARE D



Contactor, Definite Purpose, 20A, 2 pole, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open

8910DP12V09

❗ Discontinued on: 09 July 2021

❗ End-of-service on: 09 July 2021

❗ Discontinued

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	20 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DP

Complementary

Maximum Horse Power Rating	1 hp 115 V AC, 1 phase 2 hp 230 V AC, 1 phase
Locked rotor rated current	100 A 460 V AC 80 A 575 V AC 120 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Binder head

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21352-8910 DP 12
Discount Schedule	CP1B
GTIN	785901073307
Nbr. of units in pkg.	1
Package weight(Lbs)	8.64 oz (244.94 g)
Returnability	No
Country of origin	CN

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.60 in (6.604 cm)
Package 1 width	3.40 in (8.636 cm)
Package 1 Length	2.30 in (5.842 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	6.45 lb(US) (2.926 kg)
Package 2 Height	5.60 in (14.224 cm)
Package 2 width	7.20 in (18.288 cm)
Package 2 Length	7.30 in (18.542 cm)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

8910DP12V09 is replaced by:

1x		Contactor, Definite Purpose, 30A, 2 pole, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open 8910DP32V09
----	---	---