Contactor, Definite Purpose, 25A, 2 pole, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open

8910DP22V09

Discontinued on: 09 July 2021

End-of-service on: 09 July 2021

#### Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	25 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DP

#### Complementary

Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 3 hp 230 V AC, 1 phase
Locked rotor rated current	125 A 460 V AC 100 A 575 V AC 150 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208240 V AC 60 Hz 220 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Binder head

## **Environment**

Product certifications	UL Recognized CSA
Product certifications	CSA

# Ordering and shipping details

21354-8910 DP 22
CP1B
785901073321
1
8.80 oz (249.476 g)
No
CN

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

## **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	2.50 in (6.35 cm)
Package 1 width	3.40 in (8.636 cm)
Package 1 Length	2.30 in (5.842 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	6.53 lb(US) (2.962 kg)
Package 2 Height	5.50 in (13.97 cm)
Package 2 width	7.20 in (18.288 cm)
Package 2 Length	7.10 in (18.034 cm)

# Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

#### **Contractual warranty**

Warranty 18 months
--------------------

## Recommended replacement(s)

8910DP22V09 is replaced by:



Contactor, Definite Purpose, 30A, 2 pole, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open

8910DP32V09