

Product data sheet

Specifications



Contactor, Definite Purpose, 25A, 2 pole, 5 HP at 230 VAC, 1 phase, 24/24 VAC 50/60 Hz coil, open

8910DPA22V14

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	25 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase
Locked rotor rated current	125 A 460 V AC 100 A 575 V AC 150 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	24 V AC 50/60 Hz
Phase	1 phase
Electrical Connection	Binder head Quick connect terminals

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21342-8910 DPA 2_(25 AMP)
Discount Schedule	CP1B
GTIN	785901851882
Nbr. of units in pkg.	1
Package weight(Lbs)	16.32 oz (462.664 g)
Returnability	No
Country of origin	CN

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.50 in (6.35 cm)
Package 1 width	3.20 in (8.128 cm)
Package 1 Length	4.20 in (10.668 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	8.46 lb(US) (3.837 kg)
Package 2 Height	6.90 in (17.526 cm)
Package 2 width	5.60 in (14.224 cm)
Package 2 Length	8.50 in (21.59 cm)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

