

Contactor, Definite Purpose, 25A, 4 pole, 20 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA24V02

Discontinued on: 17 February 2021

End-of-service on: 17 February 2021

① Discontinued

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	25 A
Number of Poles	4P
Pole contact composition	4 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase
	10 hp 230 V AC, 3 phase
	15 hp 460 V AC, 3 phase
	20 hp 575 V AC, 3 phase
Locked rotor rated current	125 A 460 V AC
	100 A 575 V AC
	150 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz
	110 V AC 50 Hz
Phase	3 phase
Electrical Connection	Binder head
	Quick connect terminals

Environment

Product certifications	UL Recognized CSA

Ordering and shipping details

Category	21342-8910 DPA 2_(25 AMP)
Discount Schedule	CP1B
GTIN	785901080084
Nbr. of units in pkg.	1
Package weight(Lbs)	19.84 oz (562.455 g)
Returnability	No
Country of origin	CN

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.20 in (8.128 cm)
Package 1 width	3.90 in (9.906 cm)
Package 1 Length	2.90 in (7.366 cm)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

	<u> </u>	
14/ 1	40	
warranty	18 months	

Recommended replacement(s)

8910DPA24V02 is replaced by:





Contactor, Definite Purpose, 30A, 4 pole, 20 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA34V02