

Contactor, Definite Purpose, 50A, 2 pole, 10 HP at 230 VAC, 1 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA52V02

Product availability: Stock - Normally stocked in distribution facility

## Main

********	
Product or Component Type	Definite Purpose Contactor
Line Rated Current	50 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

### Complementary

Maximum Horse Power Rating	3 hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Locked rotor rated current	300 A 277 V AC 250 A 460 V AC 200 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Box lugs

#### **Environment**

Mar 17, 2022

Product certifications	UL Recognized CSA	
------------------------	----------------------	--

### Ordering and shipping details

Category	21345-8910 DPA 5_(50 AMP)
Discount Schedule	CP1B
GTIN	785901080763
Nbr. of units in pkg.	1
Package weight(Lbs)	23.04 oz (653.173 g)
Returnability	Yes
Country of origin	CN

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Life Is On Schneider

1

# **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	3.80 in (9.652 cm)
Package 1 width	4.30 in (10.922 cm)
Package 1 Length	2.70 in (6.858 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	11.83 lb(US) (5.366 kg)
Package 2 Height	8.20 in (20.828 cm)
Package 2 width	5.50 in (13.97 cm)
Package 2 Length	8.90 in (22.606 cm)

# Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

# **Contractual warranty**

Warranty	18 months

**Dimensions Drawings** 

# **Approximate Dimensions**

