

Product data sheet

Specifications



Contactor, Definite Purpose, 60A, 2 pole, 10 HP at 230 VAC, 1 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA62V02

Product availability : Stock - Normally stocked in distribution facility

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	60 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	5 hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Locked rotor rated current	360 A 277 V AC 300 A 460 V AC 240 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Box lugs

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21346-8910 DPA 6_(60 AMP)
Discount Schedule	CP1B
GTIN	785901080824
Nbr. of units in pkg.	1
Package weight(Lbs)	23.36 oz (662.245 g)
Returnability	Yes
Country of origin	CN

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.80 in (9.652 cm)
Package 1 width	4.50 in (11.43 cm)
Package 1 Length	2.70 in (6.858 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	12.05 lb(US) (5.466 kg)
Package 2 Height	8.10 in (20.574 cm)
Package 2 width	5.70 in (14.478 cm)
Package 2 Length	9.00 in (22.86 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

