Specifications

#### SQUARE D



# Contactor, Definite Purpose, 75A, 3 pole, 40 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA73RV02

Product availability: Stock - Normally stocked in distribution facility

#### Main

Product or Component Type	Definite Purpose Contactor	
Line Rated Current	75 A	
Number of Poles	3P	
Pole contact composition	3 NO	
Range of Product	DPA	

### Complementary

Maximum Horse Power Rating	5 hp 115 V AC, 1 phase 15 hp 230 V AC, 1 phase 25 hp 230 V AC, 3 phase 40 hp 460 V AC, 3 phase 40 hp 575 V AC, 3 phase
Locked rotor rated current	450 A 277 V AC 375 A 460 V AC 300 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical Connection	Quick connect terminals Box lugs
Height	3.7 in (92.8 mm)
Width	4.10 in (104.03 mm)
Depth	2.6 in (65 mm)

#### Environment

**Product Certifications** 

UL Recognized CSA

#### Ordering and shipping details

Category	US1CP1B21347
Discount Schedule	CP1B
GTIN	785901768333
Returnability	Yes

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Country of origin	CN		
Packing Units			

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.06 in (10.3 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	3.66 in (9.3 cm)
Package 1 Weight	24.000000000 oz (680.4 g)

### **Contractual warranty**

Warranty

18 months

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

```
How we assess product sustainability >
```

#### **Use Better**

S Materials and Substances	
Packaging made with recycled cardboard	Νο
Packaging without single use plastic	Νο
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	<b>REACh Declaration</b>
China RoHS Regulation	China RoHS declaration

## **Use Again**

$\bigcirc$ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	Νο