

Contactor, Definite Purpose, auxiliary contact, 3A at 120 VAC, 1 NO contact, for 50A to 90A DPA contactors

9999D10

Product availability: Stock - Normally stocked in distribution facility

#### Main

Product Range	DPA
Component type	Auxiliary Contact Module
Used with	contactor

### Complementary

Auxiliary contact composition	1 NO
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.75 A 480 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A <= 600 V AC resistive control circuit UL 508

### **Environment**

Product Certifications	CSA	
	UL Recognized	

## Ordering and shipping details

Category	21762-9999 DISCOUNT CP1B
Discount Schedule	CP1B
GTIN	785901080862
Nbr. of units in pkg.	1
Package weight(Lbs)	1.12 oz (31.752 g)
Returnability	Yes
Country of origin	CN

### **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	0.70 in (1.778 cm)
Package 1 width	1.70 in (4.318 cm)
Package 1 Length	2.80 in (7.112 cm)

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

# Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

#### **Contractual warranty**

Warranty	18 months