

Product data sheet

Specifications



TeSys GS, shaft extension, 10 x 10 x 400 mm, for 100 to 400 A GS2 switches

GS2AE21

Product availability : Stock - Normally stocked in distribution facility

Main

Range	TeSys
Device short name	GS2AE
Product or Component Type	Shaft extension
Accessory / separate part category	Control accessory
Range compatibility	TeSys GS GS2F TeSys GS GS2G TeSys GS GS2J TeSys GS GS2K TeSys GS GS2L TeSys GS GS2M TeSys GS GS2N TeSys GS GS2P TeSys GS GS2Q FuPacT GS GSC50 FuPacT GS GSB63 FuPacT GS GSD63 FuPacT GS GSB100 FuPacT GS GSC125 FuPacT GS GSD125 FuPacT GS GSD160 FuPacT GS GSB200 FuPacT GS GSB250 FuPacT GS GSD250 FuPacT GS GSB400 FuPacT GS GSD400
Switch rated current	50 A 60 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A

Complementary

Length	15.75 in (400 mm)
Shaft cross section	10 x 10 mm
Net weight	0.71 lb(US) (0.32 kg)

Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11

Web: <https://www.bolenscontrol.com/> - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

GTIN	3389119412049
Nbr. of units in pkg.	1
Package weight(Lbs)	11.01 oz (312 g)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	0.79 in (2 cm)
Package 1 Length	15.83 in (40.2 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Weight	21.38 lb(US) (9.696 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 3 Height	5.91 in (15 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to P65Warnings website
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------