



TeSys GV2 and GV3 Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, top mount, screw clamp

GVAE11

Product availability : Stock - Normally stocked in distribution facility

IVI	a	I	n	١
Ra	n	ď	6	

Range	TeSys TeSys Deca
Device short name	GVAE
Product or Component Type	Auxiliary contact block
Product Compatibility	GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2L
Mounting Location	Front side
Pole contact composition	1 NO + 1 NC
Quantity per Set	Set of 10
Complementary	
[Ui] rated insulation voltage	300 V UL 508 300 V CSA C22.2 No 14 250 V IEC 60947-1
[Ue] rated operational voltage	24240 V AC 2460 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA 110120 V AC-15 100000 cycles 120 VA 230240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

**Tightening torque** 

Rated operational power in W

12.39 lbf.in (1.4 N.m) screw clamp terminals

15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles

Height	0.43 in (11 mm)	
Width	1.77 in (45 mm)	
Depth	1.14 in (29 mm)	
Net weight	0.04 lb(US) (0.02 kg)	

## **Environment**

Environmental characteristic	Normal environment
Product certifications	UKCA

## Ordering and shipping details

Category	22367-MANUAL STR PROTECTOR - GV2
Discount Schedule	I11
GTIN	3389110343434
Nbr. of units in pkg.	1
Package weight(Lbs)	0.61 oz (17.4 g)
Returnability	Yes
Country of origin	CZ

## **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	0.63 in (1.6 cm)
Package 1 width	2.01 in (5.1 cm)
Package 1 Length	3.27 in (8.3 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	6.14 oz (174 g)
Package 2 Height	4.72 in (12 cm)
Package 2 width	2.36 in (6 cm)
Package 2 Length	2.76 in (7 cm)
Unit Type of Package 3	S02
Number of Units in Package 3	220
Package 3 Weight	9.66 lb(US) (4.383 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to P65Warnings website
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months

Connections and Schema

GVAE11