

TeSys Deca - contactor coil - LXD3 - 240 V AC 50/60 Hz for 40... 65 A contactor

LXD3U7

Product availability: Stock - Normally stocked in distribution facility

Main	
Range	TeSys
Product or Component Type	Contactor coil
Device short name	LXD3
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	240 V AC 50/60 Hz
Average resistance	202 Ohm 68 °F (20 °C)
Inductance of closed circuit	11.9 H
Product Compatibility	LC1D40AD65A LC1DT80A LC1DT60A
Mechanical durability	6 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Complementary	
Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out 0.30.6 Uc 50/60 Hz 140 °F (60 °C)) Operational 0.81.1 Uc 50 Hz 140 °F (60 °C)) Operational 0.851.1 Uc 60 Hz 140 °F (60 °C))

Con technology	Without Built in Suppliessor module
Control circuit voltage limits	Drop-out 0.30.6 Uc 50/60 Hz 140 °F (60 °C)) Operational 0.81.1 Uc 50 Hz 140 °F (60 °C)) Operational 0.851.1 Uc 60 Hz 140 °F (60 °C))
Inrush power in VA	160 VA 60 Hz 0.75 68 °F (20 °C)) 160 VA 50 Hz 0.75 68 °F (20 °C))
Hold-in power consumption in VA	15 VA 60 Hz 0.3 68 °F (20 °C)) 15 VA 50 Hz 0.3 68 °F (20 °C))
Heat dissipation	45 W 50/60 Hz

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net weight	0.15 lb(US) (0.07 kg)

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	l12
GTIN	3389119410434

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Nbr. of units in pkg.	1
Package weight(Lbs)	4.44 oz (126 g)
Returnability	Yes
Country of origin	FR
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	2.20 in (5.6 cm)
Package 1 width	3.78 in (9.6 cm)
Package 1 Length	2.20 in (5.6 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to P65Warnings website
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
PVC free	Yes
Contractual warranty	
Warranty	18 months