Product data sheet

Specifications

Green Premium™

Preventa XCS, safety switches, pivoting actuator, for metal switch

XCSZ03

Product availability : Stock - Normally stocked in distribution facility

Main

Range of Product	Telemecanique Safety switches XCS
Accessory / separate part category	Mounting and fixing accessories
Accessory / Separate Part Type	Actuator
Accessory / separate part designation	Pivoting actuator
Accessory / separate part destination	Metal guard switch

Complementary

Product Compatibility	XCSLF XCSA XCSC XCSE XCSB XCSLE
Net Weight	0.21 lb(US) (0.095 kg)

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	3389110745375
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.0 cm)
Package 1 Width	2.17 in (5.5 cm)
Package 1 Length	3.54 in (9.0 cm)
Package 1 Weight	3.67 oz (104.0 g)
Unit Type of Package 2	S02

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

Life Is On | Schneider Electric

Number of Units in Package 2	40
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	9.88 lb(US) (4.483 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to P65Warnings website.
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months

Recommended replacement(s)