



3-phase supply terminal for 3-phase busbar Size S0 and S00 connection from below

General technical data		
product brand name		SIRIUS
product designation		Three-phase feeder terminal
design of the product		Size S0/S00
size of the circuit-breaker		S00, S0
protection class IP on the front acc. to IEC 60529		IP20
touch protection on the front acc. to IEC 60529		finger-safe, for vertical contact from the front
insulation voltage with degree of pollution 3 at AC rated value	V	690
ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +60
ampacity maximum	A	63
Installation/ mounting/ dimensions		
width	mm	42.8
height	mm	73.5
depth	mm	48
Connections/ Terminals		
type of electrical connection for main current circuit		screw-type terminals
type of connectable conductor cross-sections		
• for main contacts		
— solid		1x (2.5 ... 16 mm²)
— stranded		1x (2.5 ... 25 mm²)
— finely stranded		
— with core end processing		1x (2.5 ... 16 mm²)
• at AWG cables for main contacts		1x (10 ... 4)
Certificates/ approvals		
certificate of suitability		CE / UL / CSA / CCC
General Product Approval		Declaration of Conformity
		Test Certificates



Miscellaneous

Type Test
Certificate/Test
Report

Test Certificates	Shipping Approval
-------------------	-------------------

Special Test Certificate





Shipping Approval

other



Confirmation

Further information



last modified:

12/15/2020 