SIEMENS

Data sheet

3SU1000-0BB30-0AA0



Pushbutton, 22 mm, round, plastic, yellow, pushbutton, raised, momentary contact type $\,$

product designation Pushbuttons design of the product Actuating/signaling element product type designation 3SU1 product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element Raised button principle of operation of the actuating element momentary contact type product extension optional • light source No • contact module No Yes
design of the product product type designation product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element principle of operation of the actuating element product extension optional • light source Actuating signaling element Plastic, black, 22 mm Raised butkon momentary contact type
product type designation product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element principle of operation of the actuating element product extension optional • light source 3SU1 Plastic, black, 22 mm Raised butkn Raised button momentary contact type
product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element Raised button principle of operation of the actuating element momentary contact type product extension optional • light source No
number of command points Actuator design of the actuating element principle of operation of the actuating element product extension optional • light source • light source Institute of command points 1
number of command points Actuator design of the actuating element Raised button principle of operation of the actuating element momentary contact type product extension optional • light source No
Actuator design of the actuating element principle of operation of the actuating element product extension optional • light source Raised button momentary contact type
design of the actuating element Raised button principle of operation of the actuating element momentary contact type product extension optional light source No
principle of operation of the actuating element momentary contact type product extension optional • light source No
product extension optional • light source No
• light source No
contact module Yes
color of the actuating element yellow
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 29.5 mm
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
• acc. to IEC 60068-2-27 Sinusoidal half-wave 50g / 11 ms
• for railway applications acc. to DIN EN 61373 Category 1, Class B
vibration resistance
• acc. to IEC 60068-2-6 10 500 Hz: 5g
• for railway applications acc. to DIN EN 61373 Category 1, Class B
operating frequency maximum 3 600 1/h
mechanical service life (operating cycles) typical 10 000 000
reference code acc. to IEC 81346-2
Substance Prohibitance (Date) 01.10.2014 00:00:00
Ambient conditions
ambient temperature

Web: https://www.bolenscontrol.com/ - Phone: (800) 658-5241 - Email: sales@bolenscontrol.com

-25 ... +70 °C • during operation -40 ... +80 °C • during storage environmental category during operation acc. to IEC 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %) Installation/ mounting/ dimensions height 29.5 mm width 29.5 mm shape of the installation opening round mounting diameter 22.3 mm positive tolerance of installation diameter 0.4 mm 16.2 mm mounting height installation width 29.5 mm installation depth 24.3 mm Certificates/ approvals



General Product Approval







Declaration of Conformity

Test Certificates

Marine / Shipping













Test Certificates

other

Further information





last modified: 2/11/2021 🖸