SIEMENS

Data sheet US2:52PA8A2

Metal, pushbutton 2 position Operator only Momentary Flush, red Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

| design of the product | Actuator round |
|------------------------------------|-----------------|
| Enclosure | |
| number of command points | 1 |
| delivery state as a kit | No |
| Actuator | |
| design of the actuating element | Pushbutton |
| material of the actuating element | plastic |
| shape of the actuating element | Flat pushbutton |
| type of unlocking device | without |
| number of switching positions | 2 |
| Front ring | |
| product component front ring | Yes |
| design of the front ring | standard |
| material of the front ring | metal |
| color of the front ring | chrome |
| Holder | |
| material of the holder | Metal |
| General technical data | |
| product component | |
| • light source | No |
| degree of pollution | 1 |
| protection class IP | IP66 |
| Ambient conditions | |
| ambient temperature | |
| during operation | -35 +70 °C |
| during storage | -40 +85 °C |
| Installation/ mounting/ dimensions | |
| shape of the installation opening | round |
| Certificates/ approvals | |
| * * | |

| last modified: | 6/1/2021 🖸 |
|----------------|------------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |