



*** Spare part *** LOGO! DM8 230R expansion module, PS/I/O: 230 V/230 V/relay, 2 HP 4 DI/4 DO

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
• 115 V DC	Yes
• 230 V DC	Yes
permissible range, lower limit (DC)	100 V
permissible range, upper limit (DC)	253 V
Rated value (AC)	
• 115 V AC	Yes
• 230 V AC	Yes
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	AC/DC
Input current	
• for signal "0", max. (permissible quiescent current)	0.03 mA
• for signal "1", typ.	0.08 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	50 ms
— at "1" to "0", max.	125 ms
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No
Output current	
• for signal "1" rated value	5 A
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz
• mechanical, max.	10 Hz
Relay outputs	

Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	5 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Dimensions	
Width	36 mm; 2 DU
Height	90 mm
Depth	55 mm
last modified:	3/12/2021 