

LOGO!POWER 24 V/4 A
LOGO!Power 24 V Stabilized power supply input: 100-240 V AC
output: 24 V DC/4 A



Input	
Input	1-phase AC
Rated voltage value Vin rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Wide-range input	Yes
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering at Iout rated, min.	40 ms; at Vin = 187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 120 V	1.95 A
• at rated input voltage 230 V	0.97 A
Switch-on current limiting (+25 °C), max.	30 A
I²t, max.	2.5 A²·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 16 A characteristic B or from 10 A characteristic C
Output	

Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1.5 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	10 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	20 mV
Adjustment range	22.2 ... 26.4 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	35 ms
Rated current value Iout rated	4 A
Current range	0 ... 4 A
Supplied active power typical	96 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at Vout rated, Iout rated, approx.	89 %
Power loss at Vout rated, Iout rated, approx.	12 W

Closed-loop control

Dynamic mains compensation (Vin rated ± 15 %), max.	0.2 %
Dynamic load smoothing (Iout: 10/90/10 %), Uout $\pm$ typ.	1.5 %
Load step setting time 10 to 90%, typ.	20 ms
Load step setting time 90 to 10%, typ.	20 ms

Protection and monitoring

Output overvoltage protection	Yes, according to EN 60950
Current limitation, typ.	4.7 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value • maximum	10 A
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
-----------------------------	-----

Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
CE mark	Yes
UL/cUL (CSA) approval	cULus-listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-recognized (UL 60950, CSA C22.2 No. 60950), File E151273
Explosion protection	ATEX (EX) II 3G Ex nA IIC T3
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature	
during operation	-20 ... +55 °C
— Note	with natural convection
during transport	-40 ... +70 °C
during storage	-40 ... +70 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections	
Supply input	L, N: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
Output	+, -: 2 screw terminals each for 0.5 ... 2.5 mm ²
Auxiliary	-
Width of the enclosure	90 mm
Height of the enclosure	90 mm
Depth of the enclosure	55 mm
Required spacing	
top	20 mm
bottom	20 mm
left	0 mm
right	0 mm
Weight, approx.	0.34 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15

MTBF at 40 °C	2 254 858 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)